

Mureva lights, Floodlight 30W 4000K, IP65 230V

IMT47210

Main

Range	Mureva
Range of product	Mureva lights
Product name	Floodlight
Product or component type	Lamp
Device application	Ware-houses and parking garages Residential Media device support Public areas Secure lighting Stadiums and arenas

Complementary

Type of installation	Outdoor
Total system power	30 W
Light source	LED
[Ue] rated operational voltage	230 V AC
Power factor	0.9
Colour rendering index	Ra=80
Luminous flux	3000 lm
Bulb lifespan	50000 h
Colour temperature	4000 K
Colour tint	Black
Electrical insulation class	Class F
Beam angle	110 °
Shape	Rectangular
Height	189.4 mm
Width	141.4 mm
Depth	26.5 mm
Net weight	780 g

Environment

Environmental characteristic Weatherproof

IP degree of protection	IP65
IK degree of protection	IK05
Ambient air temperature for operation	-3045 °C
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	19.8 cm
Package 1 Width	19.8 cm
Package 1 Length	19.8 cm
Package 1 Weight	750 g
Unit Type of Package 2	S04
Number of Units in Package 2	15
Package 2 Height	30 cm
Package 2 Width	40 cm
Package 2 Length	60 cm
Package 2 Weight	11.953 kg
Unit Type of Package 3	P12
Number of Units in Package 3	120
Package 3 Height	75 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	107.624 kg
Offer Sustainability	
Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty 3 years

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

WEEE