

VENICUT52



HEATNOCUT® KNITTED GLOVE - LATEX-COATED PALM Model VECUT5207





Product specifications

HEATnocut® high performance polyethylene fibre. Latex coating on palm and fingertips. Gauge 10.

 $\label{thm:cont:mance} \textbf{Support: HEAT} \textbf{nocut} \textbf{@ fibre (high performance synthetic fibres)}.$

Coating: 100% latex.

COLOUR

Yellow-Black

SIZE

07



Product Features and Benefits Good resistance to abrasion Rough finish for excellent grip on handled objects HEATnocut® High Performance Polyethylene Cut level D Good resistance to abrasion Rough finish for excellent grip on handled objects Contact heat (250°C for 15 seconds) and cut resistance Very good level of abrasion resistance



Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

3: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 3: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 2: Resistance to puncture (1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)



- 2: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

USA STANDARDS

ANSI

ANSI-ISEA 105:2016 Hand protection

A3: Resistance to cutting by sharp objects (from A1 to A9)

Item details			
Item details	Bar code	COLOUR	SIZE
VECUT5207	3295249150778	Yellow-Black	07