

VENICUTD 05



ANTISTATIC DELTANOCUT® KNITTED GLOVE - PU COATED PALM - GAUGE 18

Model VECUTD05NO06



Product specifications

DELTAnocut® high performance fibre. Polyurethane coating on palm and fingertips. Gauge 18.

Support: DELTAnocut® high performance fibres.

Coating: Solvent-free polyurethane.

COLOUR

Black

SIZE

06

Product Features and Benefits



Gauge 18

Very good dexterity and work finesse



Can be used in an ESD environment
(Electrostatic discharge hazard)

This is THE must-have cut-resistant range to
have right at your fingertips!



Cut level D

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 21420:2020 General requirements

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2020 Protective gloves against Heat (X = Unrealized test)



- X: Flame spread resistance.
- 1: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)



EN16350:2014 Protective gloves - Electrostatic properties.

3.48×10^5 : Vertical resistance in ohms (Ω) according to EN1149-2:1997

USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A4: Resistance to cutting by sharp objects (from A1 to A9)

Item details

Item details	Bar code	COLOUR	SIZE
VECUTD05NO06	3295249264246	Black	06