

## VENICUTD05



ANTISTATIC DELTANOCUT® KNITTED GLOVE - PU COATED PALM - GAUGE 18

Model VECUTD05NO08



### Product specifications

DELTAnocut® high performance fibre. Polyurethane coating on palm and fingertips. Gauge 18.

Support: DELTAnocut® high performance fibres.

Coating: Solvent-free polyurethane.

#### COLOUR

Black

#### SIZE

08

## Product Features and Benefits



Gauge 18

Very good dexterity and work finesse



Can be used in an ESD environment  
(Electrostatic discharge hazard)

This is THE must-have cut-resistant range to  
have right at your fingertips!



Cut level D

## Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 21420:2020 General requirements

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- D: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2020 Protective gloves against Heat (X = Unrealized test)



- X: Flame spread resistance.
- 1: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)



EN16350:2014 Protective gloves - Electrostatic properties.

$3.48 \times 10^5$ : Vertical resistance in ohms ( $\Omega$ ) according to EN1149-2:1997

## USA STANDARDS



ANSI-ISEA 105:2016 Hand protection

A4: Resistance to cutting by sharp objects (from A1 to A9)

## Item details

Item details	Bar code	COLOUR	SIZE
VECUTD05NO08	3295249264284	Black	08