

PVCC400



PVC GLOVES - LENGTH 40 CM

Model PVCC40010



Product specifications

Chemical PVC. PVC on interlock cotton lining. Length: 40 cm. Thickness: 1,20 - 1,40 mm.

Support: Interlock cotton.

Coating: 100% PVC.

COLOUR

Red

SIZE

10

Product Use - Risks



Biological



Wearing



Particules

CHEM D-FINDER



Product Features and Benefits



PVC

Good resistance to abrasion
Material very resistant to oils, chemicals and petroleum derivatives

Length : 40 cm

Forearm protection

Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

4: Resistance to abrasion (from 1 to 4)

1: Resistance to cutting (from 1 to 5)

3: Resistance to tear (from 1 to 4)

1: Resistance to puncture (1 to 4)

X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE B: Type B - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 3 chemicals at level 2 according to EN16523-1: 2015 (from 1 to 6).

∴ Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

A 4 > 120 mn: Méthanol (A) CAS 67-56-1

K 6 > 480 mn: Sodium hydroxide 40% (K) CAS 1310-73-2

L 6 > 480 mn: Sulphuric acid 96 % (L) CAS 7664-93-9



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.

BACTERIA ∴ BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



Item details

Item details	Bar code	COLOUR	SIZE
PVCC40010	3295249134396	Red	10