

## VENIFISH VE990



LATEX ON INTERLOCK COTTON LINING GLOVE - LENGTH: 30 CM Model VE990OR08





### Product specifications

Latex on interlock cotton lining. Rough-textured hand. Length: 30 cm. Thickness: 1,80 mm.

Support: 100% Interlock cotton. Coating: 100% natural latex.

COLOUR Orange

SIZE 8/9

### Product Use - Risks



Biological



Wearing



Particules





Product Features and Benefits				
> 1,80 MM				
100°C	Versatile glove	Resistance to chemicals and contact heat of 100°C for 15 seconds		
	Structure on very rough palm Excellent grip of very slippery ob			
	Cut cotton interlock stitched	Absorption of perspiration and moisture for improved comfort in everyday life		



#### Certifications and Standards

# $\epsilon$

#### **REGULATION (EU) 2016/425**

#### EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

#### EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 3: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

### EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

- X: Resistance to flammability (from 1 to 4)
- 1: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

# EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE A: Type A - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 6 chemicals at level 2 according to EN16523-1: 2015,

.: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

- A 6 > 480 mn: Méthanol (A) CAS 67-56-1
- K 6 > 480 mn: Sodium hydroxide 40% (K) CAS 1310-73-2
- L 4 > 120 mn: Sulphuric acid 96 % (L ) CAS 7664-93-9
- M 5 > 240 mn: Nitric acid 65% (M) CAS 7697-37-2
- N 4 > 120 mn: Acetic acid 99% (N) CAS 64-19-7
- P 6 > 480 mn: Hydrogen peroxide 30% (P) 7722-84-1
- T 6 > 480 mn: Formaldehyde 37% (T) CAS 50-00-0



# EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.

BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



#### REGULATION (EU) 1935/2004 CONTACT WITH FOOD PRODUCTS

#### GLOB MIGR Food contact - Overall Migration

.: Contact with any type of food







Item details					
Item details	Bar code	COLOUR	SIZE		
VE990OR08	3295249024123	Orange	8/9		