

VENIFISH VE990



LATEX ON INTERLOCK COTTON LINING GLOVE - LENGTH: 30 CM Model VE990OR10





Product specifications

Latex on interlock cotton lining. Rough-textured hand. Length: 30 cm. Thickness: 1,80 mm.

Support: 100% Interlock cotton. Coating: 100% natural latex.

COLOUR Orange

SIZE 10/11

Product Use - Risks



Biological



Wearing



Particules





Product Features and Benefits						
> 1,80 MM						
100°C	Versatile glove	Resistance to chemicals and contact heat of 100°C for 15 seconds				
	Structure on very rough palm	Excellent grip of very slippery objects				
	Cut cotton interlock stitched	Absorption of perspiration and moisture for improved comfort in everyday life				



Certifications and Standards

ϵ

REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

- 3: Resistance to abrasion (from 1 to 4)
- 1: Resistance to cutting (from 1 to 5)
- 2: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- X: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407:2004 Protective gloves against Heat & Fire risks (X = Unrealized test)

- X: Resistance to flammability (from 1 to 4)
- 1: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

EN ISO 374-1:2016 Protective gloves against dangerous chemicals and micro- organisms - Part 1: Terminology and performance requirements for chemical risks.

TYPE A: Type A - Water and air tightness according to EN ISO 374-2:2019. Permeation resistance to at least 6 chemicals at level 2 according to EN16523-1: 2015,

.: Determination of resistance to degradation by chemicals according to EN ISO 374-4: 2019. Part 4: Determination of resistance to degradation by chemicals.

- A 6 > 480 mn: Méthanol (A) CAS 67-56-1
- K 6 > 480 mn: Sodium hydroxide 40% (K) CAS 1310-73-2
- L 4 > 120 mn: Sulphuric acid 96 % (L) CAS 7664-93-9
- M 5 > 240 mn: Nitric acid 65% (M) CAS 7697-37-2
- N 4 > 120 mn: Acetic acid 99% (N) CAS 64-19-7
- P 6 > 480 mn: Hydrogen peroxide 30% (P) 7722-84-1
- T 6 > 480 mn: Formaldehyde 37% (T) CAS 50-00-0



EN ISO 374-5:2016 Protective gloves against dangerous chemicals and micro-organisms - Part 5: Terminology and performance requirements against micro- organisms risks.

BACTERIA + FUNGI : Water and air tightness according to EN ISO 374-2:2019.



REGULATION (EU) 1935/2004 CONTACT WITH FOOD PRODUCTS

GLOB MIGR Food contact - Overall Migration

.: Contact with any type of food







Item details						
	Item details	Bar code	COLOUR	SIZE		
	VE990OR10	3295249024147	Orange	10/11		