

DPVV736



ACRYLIC POLYAMIDE GLOVE - LATEX-COATED HAND - FOAM LATEX COATED PALM

Model DPVV736BL10



#### Product specifications

Inside: 100% acrylic gauge 10. Outside: 100% polyamide gauge 15. Full latex coating of the hand. Second foam latex coating on palm and fingertips.

Support: polyamide/ acrylic.  
Coating: Latex.

**COLOUR**  
Blue-Black

**SIZE**  
10

Product Features and Benefits

0%  
DMF



Double full latex coating

1st smooth latex coating : waterproof  
2nd foam latex coating : good adhesion



Very good resistance to cold and humidity

Ideal in cold environments down to -30°C



Brushed acrylic support

Maintenance of warmth during outdoor work  
Great comfort of use

The versatility of the protections make these gloves real assets in all climatic circumstances!

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 21420:2020 General requirements

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 2: Resistance to abrasion (from 1 to 4)
- 2: Resistance to cutting (from 1 to 5)
- 3: Resistance to tear (from 1 to 4)
- 1: Resistance to puncture (1 to 4)
- B: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN511:2006 Protective gloves against cold (X = Unrealized test)



- 1: Resistance to convective cold (from 1 to 4)
- 2: Resistance to contact cold (from 1 to 4)
- 1: Waterproof (0 or 1)

EN407:2020 Protective gloves against Heat (X = Unrealized test)



- X: Flame spread resistance.
- 2: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

Item details

| Item details | Bar code      | COLOUR     | SIZE |
|--------------|---------------|------------|------|
| DPVW736BL10  | 3295249264703 | Blue-Black | 10   |