

FIBKV02



WATER REPELLENT COWHIDE GRAIN LEATHER GLOVE PALM TURNED LINED KEVLAR® - 2 YARNS

Model FIBKV0208



Product specifications

Water-repellent cowhide full grain leather. Reverse hide cowhide full grain leather palm. 100% Kevlar® Technology knitted lining. 2 threads. Gauge 10.

Back: full grain water-repellent cowhide leather. Thickness between 1.0 and 1.2 mm.

Palm: Full grain reversed water-repellent cowhide leather. Thickness between 1 and 1.2 mm.

Lining 100% Kevlar®, 10 gauge, 2 thread.

COLOUR

Beige

SIZE

08

Product Features and Benefits

Tested according to ASTM F2675 - Test method that determines the incident energy required to cause a second-degree burn

ATPV : 53 cal/cm² on the palm



Kevlar® lining

Increased resistance to cut, tear and puncture



Water repellent treatment applied on the reverse side full grain

Ten times more effective than the grain



Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

4/4 ≥ 180 mn: Waterproofing : Ability of the glove to withstand the penetration of water, moisture.

EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 1 to 4)

2: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

3: Resistance to puncture (1 to 4)

B: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)



USA STANDARDS



ASTM-F-2675M:2013 Standard Test Method for Determining Arc Ratings of Hand Protective Products Developed and Used for Electrical Arc Flash Protection.

CAL/CM² 53 (CAL/CM²): Arc Thermal Performance Value (cal/cm²) .

Item details

Item details	Bar code	COLOUR	SIZE
FIBKV0208	3295249048549	Beige	08