

**FIBKV02**



WATER REPELLENT COWHIDE GRAIN LEATHER GLOVE PALM TURNED LINED KEVLAR® - 2 YARNS

Model FIBKV0210



#### Product specifications

Water-repellent cowhide full grain leather. Reverse hide cowhide full grain leather palm. 100% Kevlar® Technology knitted lining. 2 threads. Gauge 10.

Back: full grain water-repellent cowhide leather. Thickness between 1.0 and 1.2 mm.

Palm: Full grain reversed water-repellent cowhide leather. Thickness between 1 and 1.2 mm.

Lining 100% Kevlar®, 10 gauge, 2 thread.

#### COLOUR

Beige

#### SIZE

10

## Product Features and Benefits

Tested according to ASTM F2675 - Test method that determines the incident energy required to cause a second-degree burn

ATPV : 53 cal/cm<sup>2</sup> on the palm



Kevlar® lining

Increased resistance to cut, tear and puncture



Water repellent treatment applied on the reverse hide full grain

Ten times more effective than the grain



## Certifications and Standards



REGULATION (EU) 2016/425

EN420:2003+A1:2009 General requirements

5: Dexterity (from 1 to 5)

4/4 ≥ 180 mn: Waterproofing : Ability of the glove to withstand the penetration of water, moisture.



EN388:2016 Protective gloves against mechanical Risks (Levels obtained on the palm)

3: Resistance to abrasion (from 1 to 4)

2: Resistance to cutting (from 1 to 5)

4: Resistance to tear (from 1 to 4)

3: Resistance to puncture (1 to 4)

B: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

## USA STANDARDS



ASTM-F-2675M:2013 Standard Test Method for Determining Arc Ratings of Hand Protective Products Developed and Used for Electrical Arc Flash Protection.

CAL/CM<sup>2</sup> 53 (CAL/CM<sup>2</sup>): Arc Thermal Performance Value (cal/cm<sup>2</sup>) .

Item details

Item details	Bar code	COLOUR	SIZE
FIBKV0210	3295249048532	Beige	10