

## VV914 ARC FLASH



ELECTRIC ARC RESISTANT GLOVE

Model VV914KV08



## Product specifications

Para-aramid/Fibreglass/Modacrylic. Foam neopren coating on palm and fingertips. Gauge 10.

Support: Para-aramid/Fibreglass/Modacrylic.

Coating: Foam neopren.

## COLOUR

Yellow-Black

## SIZE

08

## Product Features and Benefits



Foam neopren

Good grip in oily, dry or wet environments  
Excellent resistance to flammability

Tested according to ASTM F2675 - Test  
method that determines the incident energy  
required to cause a second-degree burn

ATPV : 50 cal/cm<sup>2</sup> on the palm



Cut level E

## Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 21420:2020 General requirements

EN388:2016+A1:2018 Protective gloves against mechanical Risks (Levels obtained on the palm)



- 3: Resistance to abrasion (from 1 to 4)
- X: Resistance to cutting (from 1 to 5)
- 4: Resistance to tear (from 1 to 4)
- 3: Resistance to puncture (1 to 4)
- E: Resistance to cutting by sharp objects (TDM EN ISO 13997) (from A to F)

EN407: 2020 Protective gloves against Heat & Fire risks (X = Unrealized test)



- 4: Flame spread resistance.
- 2: Contact heat resistance (from 1 to 4)
- X: Convective heat resistance (1 to 4)
- X: Radiant heat resistance (from 1 to 4)
- X: Small splashes of molten metal (from 1 to 4)
- X: Large quantities of molten metal (from 1 to 4)

## USA STANDARDS



ASTM-F-2675M:2013 Standard Test Method for Determining Arc Ratings of Hand Protective Products Developed and Used for Electrical Arc Flash Protection.

CAL/CM<sup>2</sup> 50 (CAL/CM<sup>2</sup>): Arc Thermal Performance Value (cal/cm<sup>2</sup>) .

## Item details

Item details	Bar code	COLOUR	SIZE
VV914KV08	3295249266981	Yellow-Black	08