

COBRA4 S3 SRC



BOOTS WITH FLAP IN PIGMENTED SPLIT LEATHER - S3 HRO HI SRC

Model COBR4S3NO45



Product specifications

Upper: Pigmented split leather, S3 water resistant treatment. Lining: Polyester. Insock: Removable premolded - Polyamide on EVA. Outsole: Injected - PU/Rubber nitrile. • Para aramid seams. • Flap. Fastening with velcro band.

COLOUR

Black

SIZE

45

Product Features and Benefits

Standards EN ISO 20349-2: 2017 - WG special welders

Protection against thermal risks and projections
Specially designed for any multi-sector welding activity

Two elastics inside for closer fitting protection

Improved hold on the kick of the foot

Leather collar and para-aramid thread

Enhanced heat protection

Velcro closure

Fast opening
Protection against projections

Integrated flexion zones

Increased flexibility at the metatarsal level
Work facilitated whatever the position



RUBBER NITRILE OUTSOLE

Good resistance to abrasion and contact heat (standard HRO = 300°C for 1 minute)
Guaranteed insulation of the foot in the shoe against heat (HI: the temperature inside must not exceed 22°C after 30 minutes in a sand bath at +150°C)
Optimum adhesion on all types of surfaces



METAL

Certifications and Standards



REGULATION (EU) 2016/425

EN ISO 20344:2011 Personal protective equipment - Test methods for footwear

EN ISO 20345:2011 Personal protective equipment - Safety footwear.
S3 HRO HI: Additional special requirements
SRC: Slip resistance



EN ISO 20349-2:2017 Personal protective equipment. Test methods for footwear - Personal protective equipment - Footwear protecting against risks in foundries and welding - Part 2: Requirements and test methods for protection against risks in welding and allied processes.
WG: EN ISO 20349 marking code

Item details

Item details	Bar code	COLOUR	SIZE
COBR4S3NO45	3295249233433	Black	45