

KZS-2M AC B16/0.03



Specifications

ETI Code	002173104
Description	KZS-2M AC B16/0.03
Class name	RCBO
Short circuit capacity (kA)	10
Tripping characteristic	B
Rated current (A)	16
Type	AC
Rated voltage (V)	240
No. Of poles	1+N
Rated Frequency (Hz)	50/60 Hz
Standards	IEC/EN 61009
Terminals (mm ²)	1-25
Rated residual operating current I Δ n (A)	0.03
Tripping time	Instantaneous
0	

[Online product page](#) 

Other documentation



[Technical data catalogue](#)

[3D Model](#)

[Instruction manual](#)

[CE declaration](#)

[Eplan file](#)

ETIM international clasification

Classification	EC000905
Class name	Earth leakage circuit breaker
Number of poles (total)	2
Number of protected poles	1
Nominal rated voltage	230V
Rated insulation voltage Ui	500V
Nominal rated current	16A
Rated fault current	0.03A
Leakage current type	AC
Current limiting class	3
Rated short-circuit breaking capacity acc. EN 61009	10kA
Voltage type	AC
Release characteristic	B
Concurrently switching N-neutral	1
Width in number of modular spacings	2
Built-in depth	69mm
Degree of protection (IP)	IP20
Connectable conductor cross section solid-core	1...25mm ²
Connectable conductor cross section multi-wired	1...25mm ²

Dimension drawing



