

Product data sheet

Specifications



Low-Voltage Fan Coil Room Controller & Zone Controller: BACnet MS/TP, RH sensor & control, Silver Case/Fascia

SE8350U0B00

Main

Product name	SE8000 Series
Device short name	SE8300
Product or component type	Room controller
Device application	Low voltage fan coil
Net weight	340 g
AWG gauge	AWG 24...AWG 18
Targeted region	North America.
Height	120 mm
Width	86 mm
Temperature resolution	0.1 °C
Humidity measurement drift	Less than 1 % yearly
Directives	2014/30/EU - electromagnetic compatibility 2014/35/EU - low voltage directive 2014/53/EU - radio equipment directive
[In] rated current	4 A
Depth	25 mm
Ambient air temperature for operation	0...50 °C
Market segment	Lodging/hotel Small commercial Buildings Healthcare Non-critical buildings Office Residential School
Housing colour	Silver
Ambient air temperature for storage	-30...50 °C
Measurement accuracy	Temperature: +/- 0.5 °C, Humidity: +/- 5 %, 20...80 % RH (non-condensing) Humidity: +/- 10 %, 10...20 % (non-condensing) Humidity: +/- 10 %, 80...90 % (non-condensing)
Information displayed	Temperature: - 40...122 °F
Network frequency	50 Hz 60 Hz
Communication port protocol	BACnet MS/TP

	Modbus RTU
Input voltage	0...10 V DC
Temperature setting range	12...37.5 °C cooling 4.5...32 °C heating
Calibration certificate	1 pt
Output voltage	24 V AC for relay output 0...10 V DC for analog output
Relative humidity	0...95 %
Output current	1 A relay output 3 A relay output (inrush) 0.3 A universal output 1.5 A universal output (inrush)
Input type	2 x dry contact 5 x analog
Sensor type	Temperature: 10 kOhm T2 NTC thermistor Humidity: space RH sensor Humidity: bulk polymer
Output type	5 xrelay output 4 xuniversal
[Us] rated supply voltage	24 V AC 50/60 Hz +/- 15 %
Standards	EN/IEC 60730-1 FCC part 15 subpart B ICES-003 ETSI EN 300 328 ETSI EN 301 489-1:v1.9.2 FCC part 15 subpart C UL 60730-2-9 ETSI EN 301 489-17:v2.2.1, 2012
Humidity setting range	30...95 %
Range	EcoStruxure Building Expert
Economizer	Yes
Humidity control	Yes
PIR cover	No
Scheduling	No

Complementary

Surface finish	Matt
Surface treatment	Untreated
Function available	Fan control HVAC control Available with CO2/RH/T Brightness sensor Changes can be made directly over display Code lock function Easily configurable Firmware update by USB

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.8 cm
Package 1 Width	10.7 cm
Package 1 Length	15.4 cm
Package 1 Weight	500 g

Offer Sustainability

Sustainable offer status	Green Premium product
--------------------------	-----------------------

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
California proposition 65	WARNING: This product can expose you to chemicals including: LEAD, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Recommended replacement(s)