



AD916B

**RCBO 1P+N 6kA B-16A 30mA AC Class**

**Technical characteristics**

**Architecture**

Neutral position	right
Number of protected poles	1
Number of poles	2 P
Type of pole	1P+N
Curve	B

**Configuration**

Number of modules	2
-------------------	---

**Connectivity**

Top connection alignment for modular devices	Aligned terminal
--	------------------

**Main electrical features**

Rated short circuit breaking capacity $I_{cn}$ AC according IEC60898-1	6 kA
Rated operational voltage $U_e$	240 V
Frequency	50 Hz

**Voltage**

Rated insulation voltage	500 V
Max operating voltage	240 V
Rated impulse withstand voltage	4000 V

**Electric current**

Rated residual operating current	30 mA
Rated current	16 A
Withstand not tripping on 8-20 $\mu$ s wave	250 A
Breaking and opening capacity	6 kA
min/maxi threshold value of the AC thermal operation	1,13 / 1,45 $I_n$
Magnetic regulating current	3 / 5 $I_n$
Rated short circuit breaking capacity $I_{cn}$ under 230V AC according IEC60898-1	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 230V AC IEC 60947-2	6 kA
Rated ultimate short-circuit breaking capacity $I_{cu}$ under 240V AC IEC 60947-2	6 kA

**Electric current / temperature**

Rating current -25°C	18,5 A
Rating current -20°C	18,3 A
Rating current -15°C	18,1 A
Rating current -10°C	17,9 A
Rating current -5°C	17,7 A

Rating current 0°C	17,4 A
Rating current 30°C	16 A
Rating current 35°C	15,8 A
Rating current 40°C	15,6 A
Rating current 45°C	15,4 A
Rating current 50°C	15,2 A
Rating current 55°C	15 A
Rating current 60°C	14,8 A
<b>Current correction factors</b>	
Correction factor of rating current for 2 devices placed side-by-side	1
Correction factor of rating current for 3 devices placed side-by-side	0,95
Correction factor of rating current for 4 and 5 devices placed side-by-side	0,9
Correction factor of rating current for 6 devices placed side-by-side	0,85
<b>Dimensions</b>	
Depth of installed product	68 mm
Height of installed product	83 mm
Width of installed product	35 mm
<b>Frequency</b>	
Frequency	50 Hz
<b>Selectivity</b>	
Maximal rating current of downstream aM fuse for selectivity on short-circuit	2 A
Maximal rating current of downstream gL fuse for selectivity on short-circuit	6 A
Minimal rating current of upstream aM fuse for selectivity on short-circuit	20 A
Minimal rating current of upstream gL fuse for selectivity on short-circuit	20 A
<b>Power</b>	
Total power loss under I <sub>N</sub>	5,2 W
Power loss per pole at I <sub>n</sub>	3,8 W
<b>Tripping</b>	
Protected against nuisance tripping	No
<b>Endurance</b>	
Electric endurance in number of cycles	2000
Number of mechanical operations	2000
<b>Installation, mounting</b>	
Tightening torque	2,1Nm
<b>Connection</b>	
Connection cross-section at output with screw, for flexible conductor	1 / 16 mm <sup>2</sup>
Connection cross-section at output with screw, for massive conductor	1 / 25 mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 16mm <sup>2</sup>
Connection cross-sect. rigid cable	1 / 25mm <sup>2</sup>
Connection cross-section for rigid conductor, upstream terminals with screws	1 / 25 mm <sup>2</sup>

Connection cross-section of the access with screws, with flexible conductor	1 / 16 mm <sup>2</sup>
Type of connection	with screw
<b>Standards</b>	
Standard text	IEC 61009-1
European directive WEEE	concerned
<b>Safety</b>	
Protection index IP	IP20
Residual current type	AC
<b>Use conditions</b>	
Operating temperature	-25...40 °C
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I <sup>2</sup> t	3
Altitude	2000 m
Air humidity protection	for all climates
Storage/transport temperature	-25...70 °C
<b>temperatur</b>	
Temperature of calibration	30 °C