

PCE



 Illustrative photo

XREEL250 extension cord - 4xGS output with ter.

Product No

92501H48163

[See variants](#)

XREEL250 extension cord - 4xGS output with ter.

Housing material : Plastic

Type of cable used : Other

Cable cross section : 1.5 mm²

Number of cores : 3

Number of CEE sockets : 0

Number of earthing contact sockets (type F) : 4

Number of Bipasso sockets (Italy) : 0

Number of sockets 13 (Swiss) : 0

Number of Type 15 (Swiss) Outlets : 0

Number of Type 23 (Swiss) Outlets : 0

Number of Type 25 (Swiss) Outlets : 0

Cord Length : 30m

With Stand : Yes

Automatic cord rewind : No

With thermal protection : Yes

Degree of protection (IP) : IP44

CE

Housing material	Plastic	Cord length	30 m
Type of cable used	Other	With stand	Yes
Conductor cross-section	1.5mm ²	Automatic cord rewind	NO
Number of veins	3	With thermal protection	Yes
Number of protective contact sockets (type F)	4	Degree of protection (IP)	IP44

PCE POLSKA SP. Z O.O. | st. Podwalna 8a | 58-200 Dzierzoniow | Tel. 74 831 76 00 | pce@pce.pl