

PRODUCT-DETAILS

S802HV-K16

S802HV-K16 High Performance MCB



General Information

| | |
|-----------------------|--|
| Extended Product Type | S802HV-K16 |
| Product ID | 2CCF019023R0001 |
| EAN | 7612271436711 |
| Catalog Description | S802HV-K16 High Performance MCB |
| Long Description | The S802HV-K16 is a 2-pole High Performance Circuit breaker with K-characteristic, with cage terminal, long separating plates and a rated current of 16 A. It is a current limiting device with a maximum breaking capacity of 4kA at 580/1000V. It has two different tripping mechanisms, the thermal tripping mechanism for overload protection and the electromechanic tripping mechanism for short circuit protection. The S802HV-K16 complies with IEC/EN 60947-2 and allows the use for industrial applications. It can be used worldwide. The extensive range of accessory makes the use of S802HV-K16 more comfortable. Due to the fast arc extinction of S802HV-K16 your application will be secured. |

Technical

| | |
|---|--|
| Standards | IEC/EN 60947-2, UL 1077 |
| Tripping Characteristic | K |
| Rated Voltage (U_r) | acc. to IEC 60947-2 580/1000 V AC acc. to IEC 60947-2 1000 V AC |
| Rated Operational Voltage | acc. to IEC 60947-2 580/1000 V AC acc. to IEC 60947-2 1000 V AC |
| Rated Insulation Voltage (U_i) | 1000 V AC |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Input Voltage Type | AC |
| Rated Current (I_n) | 16 A |
| Rated Operational Current | 16 A |

| | |
|---|--|
| (I _e) | |
| Rated Short-Circuit Capacity | (400 V) 2.5 kA (230 V) 2.5 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I _{cu}) | (580 / 1000 V AC) 4 kA (230 V) 4 kA (400 V) 4 kA |
| Rated Conditional Short-Circuit Current (I _{nc}) | (230 V) 4 kA (400 V) 4 kA |
| Rated Service Short-Circuit Breaking Capacity (I _{cs}) | (580 / 1000 V AC) 2.5 kA |
| Frequency (f) | 60...60 Hz |
| Rated Frequency (f) | 50...60 Hz |
| Power Loss | 6.2 W at Rated Operating Conditions per Pole 3.1 W |
| Contact Position Indication | ON / OFF / TRIP |
| Energy Limiting Class | 3 |
| Number of Poles | 2 |
| Number of Protected Poles | 2 |
| Overvoltage Category | III |
| Tightening Torque | 3.5 N·m |
| Release Type | K |
| Actuator Marking | I / O |
| Housing Material | Insulation group I, RAL 7035 |
| Mounting on DIN Rail | TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715 |
| Mounting Position | Any |
| Recommended Screw Driver | Pozidriv 2 |
| Accessories Available | Yes |
| Remarks | Connection from top and bottom Connecting with CU only IP40 in enclosure with cover Cage terminal with captive screw |
| Connecting Capacity | Flexible 0...50 mm ² Rigid 0...70 mm ² |
| Terminal Type | Screw Terminals |

Environmental

| | |
|--|---|
| Ambient Temperature | -25...60 °C |
| Ambient Air Temperature | Operation -25...60 °C |
| Degree of Protection | IP20 |
| Pollution Degree | 2 |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 2 - 13.2 Hz / 1mm 13.2 - 100Hz / 0.7g with load 100% x I _e |
| Resistance to Shock acc. to IEC 60068-2-27 | 5 g 30 ms |
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | 2CCY413207D0203 |

Dimensions

| | |
|-------------------------------------|---------|
| Width in Number of Modular Spacings | 3 |
| Product Net Width | 54 mm |
| Product Net Height | 142 mm |
| Product Net Depth / Length | 82.5 mm |
| Product Net Weight | 490 g |
| Built-In Depth (t ₂) | 82.5 mm |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Units | box 1 piece |
| Package Level 1 Width | 152 mm |
| Package Level 1 Height | 99 mm |
| Package Level 1 Depth / Length | 60 mm |
| Package Level 1 Gross Weight | 580 g |
| Package Level 1 EAN | 7612271436711 |

Ordering

| | |
|------------------------|------------------|
| Minimum Order Quantity | 1 piece |
| Customs Tariff Number | 85362010 |
| E-Number (Sweden) | 2100056 |
| Country of Origin | Switzerland (CH) |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|------------------------------------|
| Declaration of Conformity - CE | 2CCC005084D0202 |
| Environmental Information | 2CCY413207D0203 |
| Instructions and Manuals | 2CCC413016M0008 |
| RoHS Information | 9AKK107680A3903 2CCC005084D0202 |

Popular Downloads

| | |
|-----------------------------------|-----------------|
| Data Sheet, Technical Information | 2CCC413003C0208 |
| Instructions and Manuals | 2CCC413016M0008 |

Classifications

| | |
|----------------------------|--|
| ETIM 7 | EC000042 - Miniature circuit breaker (MCB) |
| ETIM 8 | EC000042 - Miniature circuit breaker (MCB) |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Business |
| CN8 | 85362020 |
| eClass | V11.0 : 27141901 |
| Object Classification Code | F |

Categories

Low Voltage Products and Systems → Modular DIN Rail Products → High Performance Circuit Breakers HPCBs

