




UNIVERSAL DOWN- LIGHT PHASE recessed light

IP65, 5/8W, 2700/3000/4000/6500K, 38°, without cover

Discreet and universal: the UNIVERSAL DOWNLIGHT PHASE recessed light creates targeted lighting thanks to its narrow beam angle of 38 degrees. The IP65 protection class rating means it is protected against dirt and even jets of water. The colour temperature (2700/3000/4000/6000-K) can be selected via the CCT switch before installation. Natural colour reproduction is achieved with a CRI of over 90. And the Quick Connector Box ensures the downlight is quick and easy to install. You can also use the separately available decorative ring, which comes in white, black, gold or chrome.



TECHNICAL DATA

Item no.	1007095
IP Code	IP 20 / IP 65
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Number of through-wires	10
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	60/90 mA
Safety class	II
Wattage	8 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.003
Lumen	560 / 610 / 680 / 640 lm
Colour temperature	2700/3000/4000/6500 Kelvin
Beam angle	38 °
Color	black

Light Source

	
--	---

Accessories

1007096	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, black
1007097	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, white
1007098	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, chrome
1007099	UNIVERSAL DOWN-LIGHT Cover , for Down-light IP65, round, gold

CRI	90
LXXBXX data	L70B50
Service life	35000 h
Risk Group	0
Height	4.9 cm
Diameter	8.5 cm
Net weight	0.25 kg
Gross weight	0.268 kg
Shape of cut-out	round
Installation depth	5.5 cm
Installation diameter	6.8 cm