




GIMBLE OUT

inground fitting, LED, 3000K, stainless steel 316, 36°, IP67

The GIMBLE OUT 150 LED inground fitting with round bezel and transparent glass cover is equipped with an LED module. The head of the luminaire, which also contains the LED module, can be pulled out of the luminaire by 90°. With its IP67 protection class, the luminaire is suitable for outdoor use. The electrical connection is made directly to the 230V mains supply. This luminaire contains built-in LED lamps.



TECHNICAL DATA

Item no.	1000384
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 65 / IP 67
Impact resistance class	IK 08
Impact resistance	5 Joule
Assembly	Recessed
Assembly details	Ground, Ground with Acc.
Mechanical loading	0 t
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	600 mA
Safety class	I
Wattage	13 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Temperature at glass (light emission)	100 °C
Stroboscopic effect (SVM)	0.12
Lumen	1100 lm
Colour temperature	3000 Kelvin
Beam angle	36 °
Color	stainless steel
CRI	80
LXXBXX data	L70B50

Light Source

916450	
--------	---

Accessories

1000655	Inground mounting pot , black for DASAR® PRE- MIUM and GIMBLE OUT
228730	CONNECTION BOX , 3-pin, IP68
233792	Inground mounting pot , with cover for DASAR PREMIUM and GIMBLE OUT DN160

Service life	35000 h
Height	13.1 cm
Diameter	18 cm
Net weight	3.058 kg
Gross weight	3.279 kg
Shape of cut-out	round
Installation depth	17 cm
Installation diameter	15 cm
BIG WHITE Page	724