





TRUST 30

outdoor floor stand, LED, 3000K, IP55, stainless steel 316, Ø/H 6/30 cm, 8.6W

With the stainless steel TRUST 30 floor stand, the opalescent PC light surface is enclosed by a stainless steel cap. With protection class IP55, it is suitable for outdoor use. As an option an earth spike as well as a connection box for safe electrical connection to the round luminaire upright, are available. The electrical connection of the luminaire, which comes in two sizes, is directly to the 230V mains supply. A stainless-steel grid is available as a further accessory to change the lighting effect. The TRUST series contains other wall lights and can therefore be used universally. This luminaire is fitted with a powerful 8.6W LED.





TECHNICAL DATA

Item no.	228100	
Number of different light outlets	1	
IP Code	IP 55	
Impact resistance class	IK 07	
Impact resistance	2 Joule	
Assembly	Surface	
Assembly details	Ground	
Primary nominal voltage	220-240V ~50/60Hz	
Safety class	1	
Wattage	9 W	
Minimum ambient temperature	-20 °C	
Maximum ambient temperature	40 °C	
Stroboscopic effect (SVM)	3.25	
Lumen	400 lm	
Lumen Colour temperature	400 lm 3000 Kelvin	
Colour temperature	3000 Kelvin	
Colour temperature Color	3000 Kelvin stainless steel	
Colour temperature Color CRI	3000 Kelvin stainless steel 80	
Colour temperature Color CRI LXXBXX data	3000 Kelvin stainless steel 80 L70B50	
Colour temperature Color CRI LXXBXX data Service life	3000 Kelvin stainless steel 80 L70B50 30000 h	
Colour temperature Color CRI LXXBXX data Service life Light distribution	3000 Kelvin stainless steel 80 L70B50 30000 h rotational symmetric	



Light Source

709322		Diameter	6 cm
Accessories		Net weight	1.476 kg
1000449	GRID for Trust stainless steel	Gross weight	1.749 kg
		BIG WHITE Page	559
227922	EARTH SPIKE , for TRUST, NAILS, BIG NAILS, BIG NAILS PLUS and ENERGY PACK, length 50cm		
228130	GRID 316 , for TRUST outdoor floor stand, stain- less steel 316		
228730	CONNECTION BOX , 3-pin, IP68		