



NEW TRIA 2 SET

recessed fitting, double-headed LED, 2700K, rectangular, matt black, 38°, 15W, incl. driver, clip springs

The simplicity and effectiveness of the innovative NEW TRIA 2 SET is captivating. It is available in matt black, white, or brushed aluminium, in round or square form as well as single-headed or as multi-lamp. Equipped with two powerful, warm white premium COB LEDs in a tiltable mount, as well as LED driver included in the scope of supply, the set can be used in any lighting situation. The electrical connection is made directly to the 230V mains supply.



TECHNICAL DATA

Item no.	113890
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	14 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	30 °C
Level of inrush current	5 A
Duration of inrush current	33 µs
Stroboscopic effect (SVM)	0.05
Lumen	1160 lm
Colour temperature	2700 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50
Service life	40000 h
Length	17 cm
Width	9 cm

Light Source

916320	
--------	---

Height	3.9 cm
Net weight	0.438 kg
Gross weight	0.505 kg
Shape of cut-out	square
Installation length	15.5 cm
Installation width	8 cm
Installation depth	4 cm
BIG WHITE Page	364