




## KADUX 1 SET

recessed fitting, single-headed LED, 3000K, square, matt black, 38°, 9W, incl. driver

The KADUX recessed fitting series has a robust housing with appealing, high-quality looks. This LED set is multi-directional, allowing individual focus of the light beam. The KADUX 1 SET comes ready for direct connection to 230V mains and is available in matt black, matt white or brushed aluminium, as well as in single, double, or triple-headed variations.



## TECHNICAL DATA

Item no.	115700
Rotating or tilting	cardanic
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	7.5 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Level of inrush current	2 A
Duration of inrush current	40 µs
Stroboscopic effect (SVM)	0.02
Lumen	650 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	80
LXXBXX data	L70B50

## Light Source

916451	
--------	---

<b>Service life</b>	40000 h
<b>Length</b>	9 cm
<b>Width</b>	9 cm
<b>Height</b>	8.5 cm
<b>Net weight</b>	0.379 kg
<b>Gross weight</b>	0.432 kg
<b>Shape of cut-out</b>	square
<b>Installation length</b>	8 cm
<b>Installation width</b>	8 cm
<b>Installation depth</b>	8 cm
<b>BIG WHITE Page</b>	379