





CONTONE

recessed fitting, LED, 2000-3000K, round, white, tiltable, 13W, including leaf springs

With the CONTONE recessed ceiling light you can set the lighting mood however you desire. When dimming the built-in premium COB LED module, the colour of light changes from 3000K to 2000K, which is the same effect as when dimming a filament lamp. The electrical connection is made directly to the 230V mains supply thanks to the built-in LED driver.



TECHNICAL DATA

Item no.	161271
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	350 mA
Safety class	II
Wattage	15 W
Level of inrush current	10 A
Duration of inrush current	40 µs
Lumen	1000 lm
Colour temperature	2000-3000 Kelvin
Beam angle	30 °
Color	white
CRI	90
LXXBXX data	L70B50
Service life	40000 h
Light distribution	rotational symmetric
Light outlet	direct
Height	13.7 cm

Light Source

916619	
--------	---

Diameter	9.2 cm
Net weight	0.334 kg
Gross weight	0.414 kg
Shape of cut-out	round
Installation depth	13.5 cm
Installation diameter	8.2 cm
BIG WHITE Page	398