




DOWNUNDER OUT LED L

outdoor recessed wall light, LED, 3000K, anthracite

The DOWNUNDER OUT LED L recessed wall light is made of aluminium, and outfitted with high output SMD LEDs that produce downward directed, glare-free light emission. Thanks to its IP55 protection class, the luminaire is suitable for outdoor use. The luminaire is connected directly to the 230V mains supply. A mounting pot is included in the delivery for simple assembly.



TECHNICAL DATA

Item no.	233615
IP Code	IP 55
Assembly	Recessed
Assembly details	Wall
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	300 mA
Safety class	I
Wattage	3.3 W
Minimum ambient temperature	-25 °C
Maximum ambient temperature	50 °C
Stroboscopic effect (SVM)	0
Lumen	85 lm
Colour temperature	3000 Kelvin
Color	anthracite
CRI	80
LXXBXX data	L70B50
Service life	25000 h
Width	14 cm
Height	14 cm
Depth	5 cm
Net weight	0.499 kg
Gross weight	0.571 kg

Light Source

916417		Shape of cut-out	square
		Installation length	12.8 cm
		Installation width	11.1 cm
		Installation depth	7 cm
		BIG WHITE Page	701