




KALU

wall and ceiling light, double-headed, QPAR111, round, matt white, max. 150 W

The puristic design of KALU ceiling light is a guarantor for absolutely individual alignment of lamp heads, optionally equipped with halogen or suitable LED ES111 lamps. The light can also be dimmed which offers even more installation possibilities. Available in several colour versions KALU ceiling light is supplied ready for direct connection to 230V mains supply.



TECHNICAL DATA

Item no.	147311
Lamp	QPAR111
Number of sockets	2
Lamps included	No
Tilt range	90 °
Horizontal rotation range	350 °
Rotating or tilting	rotary Bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Ceiling,Wall
Primary nominal voltage	220-240V ~50/60Hz
Safety class	I
Wattage	75 W
Maximum ambient temperature	40 °C
Color	white
Light outlet	direct
Length	30 cm
Width	9 cm
Height	18 cm
Net weight	0.951 kg
Gross weight	1.268 kg
BIG WHITE Page	304

Recommended lamp

1005274	QPAR111 GU10 , transparent LED light, 8W 2700K CRI90 38°
1005297	LED light , QPAR111 GU-10 12W 670lm 2700K CRI90 55° dimmable
1005298	LED light , QPAR111 GU-10 12W 680lm 3000K CRI90 55° dimmable
1005299	LED light , QPAR111 GU-10 12W 750lm 4000K CRI90 55° dimmable