

Eaton 137308

Catalog Number: 137308

Eaton Distribution parts. Installation contactor, 24 VAC/DC, 4N/O, 25A

General specifications

Product Name	Catalog Number
Eaton Distribution parts	137308
Model Code	EAN
CMUC24/25-40	4015081341801
Product Length/Depth	Product Height
85 mm	60 mm
Product Width	Product Weight
35 mm	.22 kg
Compliances	
RoHS conform	



Product specifications

Rated operating voltage (Ue) - min

440 V

Rated operational current for specified heat dissipation (In)

25 A

Ambient operating temperature - max

60 °C

Heat dissipation per pole, current-dependent

0 W

Load fluorescent lamp - max

1360 VA

Built-in depth

69.5 mm

Number of modular spacings

2

Features

Additional equipment possible

Hum-free

Heat dissipation capacity

0 W

Load fluorescent lamp (duo circuit) - max

2552 VA

Amperage Rating

25 A

Voltage rating (excitation) - max

26.4 V

Incandescent lamp load - max

3000 W

Ambient operating temperature - min

-40 °C

Voltage rating (excitation) - min

20.4 V

Number of contacts (normally open contacts)

4

Equipment heat dissipation, current-dependent

11.5 W

Resources

Certification reports

DA-DC-03_CMUC

Drawings

eaton-3d-drawing-sch-pack.jpg

eaton-3d-drawing-z-r-sch-einbau.jpg

Mas_sc

eaton-wiring-diagram-z-sch-klem-bez4.jpg

sch_pack

Z_R_SCH_Einbau

Wiring diagrams

Z_SCH_Klem_bez4

Rated operating voltage (Ue) - max

440 V

Load fluorescent lamp (parallel compensated) - max

1360 VA

Number of contacts (normally closed contacts)

0

Static heat dissipation, non-current-dependent

0 W

Utility category

0

Voltage type

AC/DC

Degree of protection

IP20



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)