TORES LED PC

GENERAL CARD



TECHNICAL PARAMETERS

Ingress protection: IP65

Luminous flux [lm]*: 5000; 7100; 7200; 10100

Colour temperature [K]: 4000

Material of the body: PC

Colour of the body: grey

Diffuser material: PC

Diffuser type: frozen

Mounting version: surface, suspended

Dimensions (H/W/T/S) [mm]: 1200/85/80; 1500/85/80;

CHARACTERISTICS

Tores LED PC is a lamp dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Its very good technical parameters guarantee the achievement of the required level of illumination and energy savings. The lamp has a number of improvements to make installation easier and faster, such as adjustable brackets that provide an installation tolerance of +/-50 mm. As standard, it is equipped with durable stainless steel (INOX) clips. The lamp has a high IP65 rating, and the lamp body and shade are UV resistant.

APPLICATION

Multifunctional surface-mounted LED lamp is designed for use in areas with high requirements for dust- and waterproofing. Particularly recommended for illuminating industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underpasses. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions.



TORES LED PC

GENERAL CARD

AVAILABLE VERSIONS



TORES LED PC 36W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
36	4000	5000	1200/85/80	<u>>> 374166</u>

TORES LED PC 50W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
50	4000	7100	1200/85/80	>> 374173
50	4000	7200	1500/85/80	>> 374227

TORES LED PC 70W

Rated power of the luminaire [W]*	Colour temperature [K]	Luminous flux [lm]*	Dimensions (H/W/T/S) [mm]	Index
70	4000	10100	1500/85/80	<u>>> 374180</u>

Card creation date: 09 February 2023



