



Ledinaire floodlights gen3

BVP164 LED60/840 PSU 50W SWB MDU CE

- - - 840 neutral white - - - Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

Product data

Operating and electrical		Optical cover/lens type	
Input Voltage	220 to 240 V	Optical cover/lens type	Glass
Line Frequency	50 or 60 Hz	Luminaire light beam spread	110° x 110°
Input frequency	50 or 60 Hz	Control interface	-
Initial CLO power consumption	- W	Connection	Flying leads/cables
Average CLO power consumption	50 W	Cable	Cable 1.0 m without plug
Power Consumption	50 W	Protection class IEC	Safety class I
End CLO power consumption	- W	Flammability mark	-
Inrush current	1.68 A	CE mark	Yes
Inrush time	0.0082 ms	ENEC mark	-
Power Factor (Fraction)	0.9	Warranty period	3 years
General information		Optic type outdoor	Symmetrical
Lamp family code	-	Constant light output	No
Light source colour	840 neutral white	Number of products on MCB of 16 A type B	44
Light source replaceable	No	Photobiological risk	Photobiological risk group 1 @200mm to EN62778
Number of gear units	Unit	Photobiological risk specification	0.2 m
Driver/power unit/transformer	-	EU RoHS compliant	Yes
Driver included	Yes	Light source engine type	LED
		Lighting Technology	LED


Ledinaire floodlights gen3

Brand	Philips
Light technical	
Upwards light output ratio	0
Luminous Flux	6,000 lm
Standard tilt angle post-top	-
Standard tilt angle side entry	-
Luminous Efficacy (rated) (Nom)	120 lm/W
Colour rendering index (CRI)	>80
Temperature	
Ambient temperature range	-20 to +40 °C
Mechanical and housing	
Housing material	Aluminium die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Housing Colour	Grey
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	173 mm
Overall width	263 mm
Overall height	53 mm
Effective projected area	0.028 m ²
Dimensions (height x width x depth)	NaN x NaN x NaN mm
Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge Protection (Common/Differential)	2/2 kV

Sustainability rating	-
Initial performance (IEC compliant)	
Luminous flux tolerance	+/-10%
Init. Corr. Colour Temperature	4000 K
Initial chromaticity	(0.380, 0.380) SDCM <5
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2
Over time performance (IEC compliant)	
Control gear failure rate at median useful life 50,000 h	5 %
Lumen maintenance at median useful life* 50,000 h	80
Application conditions	
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable
Product data	
Full EOC	871951453475999
Order product name	BVP164 LED60/840 PSU 50W SWB MDU CE
Order code	53475999
SAP numerator – quantity per pack	1
Numerator – packs per outer box	16
Material number (12NC)	911401884683
Net weight	0.890 kg
Full product name	BVP164 LED60/840 PSU 50W SWB MDU CE
EAN/UPC - Case	8719514534858



Dimensional drawing



Ledinaire floodlights gen3

