



MASTER PL-S 4 Pin



MASTER PL-S 9W/830/4P 1CT/5X10BOX

Energy-saving compact fluorescent lamps. Compact long-arc low-pressure mercury discharge lamp. Envelope consists of 2 parallel narrow fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied HF control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General information	
Cap base	2G7 [2G7]
Life to 50% failures preheat (nom.)	13000 h
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	98 %
LSF preheat 6,000 hours rated	97 %
LSF preheat 8,000 hours rated	92 %
LSF preheat 16,000 hours rated	30 %
	Sphere

Light technical	
Colour Code	830 [CCT of 3,000 K]
Luminous flux (nom.)	590 lm
Luminous flux (rated) (nom.)	583 lm
Colour designation	Warm white (WW)
Chromaticity coordinate X (nom.)	0.44
Chromaticity coordinate Y (nom.)	0.403

Correlated Colour Temperature (Nom)	3000 K
Luminous efficacy (rated) (nom.)	73 lm/W
Colour rendering index (nom.)	82
LLMF 2000 h Rated	95 %
LLMF 4000 h Rated	92 %
LLMF 6000 h Rated	90 %
LLMF 8000 h Rated	88 %
LLMF 12000 h Rated	86 %

Operating and electrical	
Power (Rated) (Nom)	8.8 W
Lamp current (nom.)	0.170 A

Temperature	
Design temperature (nom.)	28 °C

MASTER PL-S 4 Pin

Controls and dimming

Dimmable	Yes
----------	-----

Mechanical and housing

Cap-base information	4P
----------------------	----

Approval and application


Energy Efficiency Class	G
Mercury (Hg) content (max.)	1.4 mg
Mercury (Hg) content (nom.)	1.4 mg
Energy consumption kWh/1,000 hours	9 kWh
	423593

Product data

Full product code	871150026093270
-------------------	-----------------

Order product name	MASTER PL-S 9W/830/4P 1CT/5X10BOX
EAN/UPC – product	8711500260932
Order code	26093270
Local order code	PLS98304P
SAP numerator – quantity per pack	1
Local code description	8344618
Numerator – packs per outer box	50
SAP material	927936283011
Net Weight (Piece)	30.000 g
ILCOS code	FSD-9/30/1B-E-2G7


Dimensional drawing




Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-S 9W/830/4P 1CT/ 5X10BOX	28 mm	13 mm	128 mm	145 mm	151.1 mm

MASTER PL-S 9W/830/4P 1CT/5X10BOX

Photometric data




Lightcolour /830



Lightcolour /830

MASTER PL-S 4 Pin

Lifetime



LDLE_PLS4PLM_0001-Life expectancy diagram

LDLE_PLS4PLM_0002-Life expectancy diagram



LDLM_PLS4PLM_0001-Lumen maintenance diagram

