

# Eaton 112873

Catalog Number: 112873

Eaton Moeller series xPole - PFL6/7 RCBO - residual-current circuit breaker with overcurrent protection. RCD/MCB, 10A, 30mA, MCB trip curve B, 1pole+N, RCCB trip type: A, PFL6

## General specifications

<b>Product Name</b>	<b>Catalog Number</b>
Eaton Moeller series xPole - PFL6/7 RCBO - residual-current circuit breaker with overcurrent protection	112873 EAN 4015081124183
<b>Product Length/Depth</b>	<b>Product Height</b>
86 mm	75 mm
<b>Product Width</b>	<b>Product Weight</b>
37 mm	0.225 kg
<b>Compliances</b>	<b>Certifications</b>
CE Marked RoHS conform	CE
	<b>Model Code</b> PFL6-10/1N/B/003-A

## Delivery program

### Application

Switchgear for residential and commercial applications

### Basic function

Combined RCD/MCB devices

### Product application

Switchgear for industrial and advanced commercial applications

### Number of poles

Single-pole + N

### Number of poles (protected)

1

### Number of poles (total)

2

### Release characteristic

B

### Rated current

10 A

### Fault current rating

0.03 A

### Type

RCBO

## Technical data - electrical

### Voltage type

AC

### Voltage rating

230 V

### Rated operational voltage (U<sub>e</sub>) - max

230 V

### Rated insulation voltage (U<sub>i</sub>)

440 V

### Rated impulse withstand voltage (U<sub>imp</sub>)

4 kV

### Frequency rating

50 Hz

### Leakage current type

A

### Rated short-circuit breaking capacity (EN 60947-2)

0 kA

### Rated short-circuit breaking capacity (EN 61009)

6 kA

### Rated short-circuit breaking capacity (EN 61009-1)

6 kA

### Rated short-circuit breaking capacity (IEC 60947-2)

0 kA

### Surge current capacity

0.25 kA

### Disconnection characteristic

Undelayed

### Overvoltage category

III

### Pollution degree

2

## Technical data - mechanical

### Width in number of modular spacings

2

## Design verification as per IEC/EN 61439 - technical data

### Rated operational current for specified heat dissipation (I<sub>n</sub>)

10 A

#### Built-in depth

69.5 mm

#### Degree of protection

IP20

#### Connectable conductor cross section (solid-core) - min

1 mm<sup>2</sup>

#### Connectable conductor cross section (solid-core) - max

25 mm<sup>2</sup>

#### Connectable conductor cross section (multi-wired) - min

1 mm<sup>2</sup>

#### Connectable conductor cross section (multi-wired) - max

25 mm<sup>2</sup>

#### Heat dissipation per pole, current-dependent

0 W

#### Equipment heat dissipation, current-dependent

2.5 W

#### Static heat dissipation, non-current-dependent

0 W

#### Heat dissipation capacity

0 W

#### Ambient operating temperature - min

-25 °C

#### Ambient operating temperature - max

40 °C

## Design verification as per IEC/EN 61439

### 10.2.2 Corrosion resistance

Meets the product standard's requirements.

### 10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

### 10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

### 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

### 10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

### 10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

### 10.2.7 Inscriptions

Meets the product standard's requirements.

### 10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

### 10.4 Clearances and creepage distances

## Additional information

### Current limiting class

3

### Features

Concurrently switching N-neutral

## Resources

### Catalogs

[eaton-xpole-pf17-rcbo-catalog-ca019045en-en-us.pdf](#)

[eaton-xpole-pf16-rcbo-catalog-ca019046en-en-us.pdf](#)

### User guides

[eaton-xpole-combined-mcb-rcd-device-rcbo-packaging-manual-multilingual.pdf](#)

IL019140ZU

Meets the product standard's requirements.

#### 10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

#### 10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

#### 10.8 Connections for external conductors

Is the panel builder's responsibility.

#### 10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

#### 10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

#### 10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

#### 10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

#### 10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

#### 10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.



Eaton Corporation plc  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

© 2023 Eaton. All rights reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)