

Eaton 286500

Catalog Number: 286500

Eaton Moeller series xPole - PF6/7 RCCB. PF6, 2 pole, In: 63 A, Icn: 6 kA, IΔN: 0.03 A, Type AC, AC current sensitive, Partly surge-proof 250 A, residential and commercial

General specifications

Product Name	Catalog Number
Eaton Moeller series xPole - PF6/7 RCCB	286500
	Model Code
	PF6-63/2/003
EAN	Product Length/Depth
4015082865009	80 mm
Product Height	Product Width
71 mm	35 mm
Product Weight	Compliances
.22 kg	RoHS conform
Certifications	
IEC/EN 61008	

Product specifications

Rated operational current for specified heat dissipation (In)

63 A

10.11 Short-circuit rating

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Permitted storage and transport temperature - min

-35 °C

10.4 Clearances and creepage distances

Meets the product standard's requirements.

10.12 Electromagnetic compatibility

Is the panel builder's responsibility. The specifications for the switchgear must be observed.

Mounting Method

Quick attachment with 2 latch positions for DIN-rail IEC/EN

60715

DIN rail

Amperage Rating

63 A

10.2.5 Lifting

Does not apply, since the entire switchgear needs to be evaluated.

Rated fault current - max

.03 A

Test circuit range

184 V AC - 250 V AC

10.2.3.1 Verification of thermal stability of enclosures

Meets the product standard's requirements.

Tripping time

Non-delayed

Fitted with:

Interlocking device

IS/SPE-1TE 101911

Rated residual making and breaking capacity

630 A

Frequency rating

50 Hz

Resources

Application notes

[eaton-rcd-application-guide-br019003en-en-us.pdf](#)

Catalogs

[eaton-xpole-pf7-rcb-catalog-ca019032en-en-us.pdf](#)

[eaton-xpole-pf6-rcb-catalog-ca019034en-en-us.pdf](#)

Certification reports

[DA-DC-03_Pf6](#)

Drawings

[eaton-circuit-breaker-xeffect-frcmm-rcb-dimensions.jpg](#)

[FRCmM_Conn_1](#)

[eaton-xpole-pf6/7-rcb-3d-drawing.jpg](#)

Installation instructions

[IL019140ZU](#)

Wiring diagrams

[eaton-xpole-pf6/7-rcb-wiring-diagram.jpg](#)

[Mas_PFIM](#)

[PF7_2P](#)

10.8 Connections for external conductors

Is the panel builder's responsibility.

Fault current rating

30 mA

Terminal protection

Finger and hand touch safe, DGUV VS3, EN 50274

Special features

Maximum operating temperature is 60 °C: Starting at 40 °C, the max. permissible continuous current decreases by 1.8% for every 1 °C

Tripping signal contact for subsequent installation Z-NHK
248434

Sensitivity type

AC current sensitive

Ambient operating temperature - max

60 °C

Heat dissipation per pole, current-dependent

0 W

Climatic proofing

25-55 °C / 90-95% relative humidity according to IEC 60068-2

Built-in depth

69.5 mm

Short-circuit rating

63 A (max. admissible back-up fuse)

Features

Additional equipment possible

Residual current circuit breaker

Lifespan, electrical

4000 operations

Connectable conductor cross section (solid-core) - min

1.5 mm²

10.9.3 Impulse withstand voltage

Is the panel builder's responsibility.

Number of poles

Two-pole

Terminal capacity (solid wire)

1.5 mm² - 35 mm²

Ambient operating temperature - min

-25 °C

10.6 Incorporation of switching devices and components

Does not apply, since the entire switchgear needs to be evaluated.

Rated short-circuit strength

6 kA

10.5 Protection against electric shock

Does not apply, since the entire switchgear needs to be evaluated.

Used with

PF6

Type AC

Residual current circuit breakers

KLV-TC-2 276240 (Compact enclosure)

Z-FW/LP 248296 (Remote control and automatic switching device)

Z-RC/AK-2TE 285385 (sealing cover set)

Equipment heat dissipation, current-dependent

9.7 W

10.13 Mechanical function

The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

10.2.6 Mechanical impact

Does not apply, since the entire switchgear needs to be evaluated.

10.9.4 Testing of enclosures made of insulating material

Is the panel builder's responsibility.

Static heat dissipation, non-current-dependent

0 W

Application

Residual current circuit breaker for residential and commercial applications

xPole - Switchgear for residential and commercial applications

10.3 Degree of protection of assemblies

Does not apply, since the entire switchgear needs to be evaluated.

Voltage type

AC

Terminal capacity (stranded cable)

16 mm² (2x)

Leakage current type

AC

Frame

45 mm

Built-in width (number of units)

35 mm (2 SU)

Terminals (top and bottom)

Open mouthed/lift terminals

Heat dissipation capacity

0 W

Impulse withstand current

Partly surge-proof 250 A

Width in number of modular spacings

2

Busbar material thickness

0.8 mm - 2 mm

10.2.3.2 Verification of resistance of insulating materials to normal heat

Meets the product standard's requirements.

10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects

Meets the product standard's requirements.

Lifespan, mechanical

20000 operations

Voltage rating

230 V AC

10.9.2 Power-frequency electric strength

Is the panel builder's responsibility.

Connectable conductor cross section (solid-core) - max

35 mm²

Degree of protection

IP20, IP40 with suitable enclosure

IP20

Rated short-time withstand current (I_{cw})

6 kA

Accessories required

Z-HK 248432

Pollution degree

2

10.7 Internal electrical circuits and connections

Is the panel builder's responsibility.

Connectable conductor cross section (multi-wired) - min

1.5 mm²

Rated impulse withstand voltage (Uimp)

4 kV

10.10 Temperature rise

The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.

Connectable conductor cross section (multi-wired) - max

16 mm²

Type

PF6

Residual current circuit breakers

Type AC

10.2.2 Corrosion resistance

Meets the product standard's requirements.

10.2.4 Resistance to ultra-violet (UV) radiation

Meets the product standard's requirements.

10.2.7 Inscriptions

Meets the product standard's requirements.

Surge current capacity

.25 kA

Permitted storage and transport temperature - max

60 °C

Admissible back-up fuse overload - max

40 A gG/gL

Rated fault current - min

.03 A

Rated operational voltage (Ue) - max

230 V

Rated insulation voltage (Ui)

440 V



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)