

LED element, white, front mount, 85-264VAC



Part no. M22-LED230-W
216563
EL Number 4355375
(Norway)

| | |
|--|--|
| Product name | Eaton Moeller® series M22 Accessory LED |
| Part no. | M22-LED230-W |
| EAN | 4015082165635 |
| Product Length/Depth | 38 millimetre |
| Product height | 10 millimetre |
| Product width | 37 millimetre |
| Product weight | 0.011 kilogram |
| Compliances | CE Marked |
| Certifications | EN 60947-5 CSA Std. C22.2 No. 14-05 UL 508 CSA Std. C22.2 No. 94-91 IEC 60947-5 VDE CE CSA File No.: 012528 UL File No.: E29184 CSA-C22.2 No. 14-05 UL CSA-C22.2 No. 94-91 CSA IEC 60947-5-1 CSA Class No.: 3211-03 IEC/EN 60947-5 UL Category Control No.: NKCR |
| Product Tradename | M22 |
| Product Type | Accessory |
| Product Sub Type | LED |
| Color | White |
| Fitted with: | Diode Light source |
| Light color | White |
| Degree of protection | IP20 |
| Lifespan, electrical | 100,000 h (at 25°C, according to EN60064) |
| Operating torque | 0.8 N-m |
| Overvoltage category | III |
| Pollution degree | 3 |
| Rated impulse withstand voltage (Uimp) | 6000 V AC |
| Voltage type | AC |
| Mounting position | As required |
| Shock resistance | 30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms Mechanical, According to IEC/EN 60068-2-27 |
| Ambient operating temperature - min | -25 °C |
| Ambient operating temperature - max | 70 °C |
| Ambient storage temperature - min | 40 °C |
| Ambient storage temperature - max | 80 °C |
| Climatic proofing | Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30 |
| Terminal capacity (solid) | 0.75 - 2.5 mm ² |
| Terminal capacity (stranded) | 0.5 - 2.5 mm ² |

| | | |
|--|--|--|
| Power consumption | | Max. 0.33 W |
| Rated insulation voltage (Ui) | | 500 V |
| Rated operational current (Ie) - min | | 5 A |
| Rated operational current (Ie) - max | | 15 A |
| Rated operational voltage (Ue) at AC - max | | 264 V |
| Rated operational voltage (Ue) at AC - min | | 85 V |
| Rated operational voltage (Ue) at DC - max | | 0 V |
| Rated operational voltage (Ue) at DC - min | | 0 V |
| Connection to SmartWire-DT | | No |
| Connection type | | Front fixing |
| Force for positive opening - min | | 0 N |
| Equipment heat dissipation, current-dependent Pvid | | 0 W |
| Heat dissipation capacity Pdis | | 0 W |
| Heat dissipation per pole, current-dependent Pvid | | 0 W |
| Rated operational current for specified heat dissipation (In) | | 0 A |
| Static heat dissipation, non-current-dependent Pvs | | 1 W |
| 10.2.2 Corrosion resistance | | Meets the product standard's requirements. |
| 10.2.3.1 Verification of thermal stability of enclosures | | Meets the product standard's requirements. |
| 10.2.3.2 Verification of resistance of insulating materials to normal heat | | Meets the product standard's requirements. |
| 10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects | | Meets the product standard's requirements. |
| 10.2.4 Resistance to ultra-violet (UV) radiation | | Meets the product standard's requirements. |
| 10.2.5 Lifting | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.6 Mechanical impact | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.2.7 Inscriptions | | Meets the product standard's requirements. |
| 10.3 Degree of protection of assemblies | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.4 Clearances and creepage distances | | Meets the product standard's requirements. |
| 10.5 Protection against electric shock | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.6 Incorporation of switching devices and components | | Does not apply, since the entire switchgear needs to be evaluated. |
| 10.7 Internal electrical circuits and connections | | Is the panel builder's responsibility. |
| 10.8 Connections for external conductors | | Is the panel builder's responsibility. |
| 10.9.2 Power-frequency electric strength | | Is the panel builder's responsibility. |
| 10.9.3 Impulse withstand voltage | | Is the panel builder's responsibility. |
| 10.9.4 Testing of enclosures made of insulating material | | Is the panel builder's responsibility. |
| 10.10 Temperature rise | | The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices. |
| 10.11 Short-circuit rating | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.12 Electromagnetic compatibility | | Is the panel builder's responsibility. The specifications for the switchgear must be observed. |
| 10.13 Mechanical function | | The device meets the requirements, provided the information in the instruction leaflet (IL) is observed. |

Technical data ETIM 8.0

| | | |
|---|---|----------|
| Low-voltage industrial components (EG000017) / Lamp holder block for control circuit devices (EC000204) | | |
| Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Bulb socket block for command and alarm devices (ecl@ss10.0.1-27-37-12-09 [AKF027014]) | | |
| Transformer integrated | | No |
| With integrated voltage decreasing resistor | | No |
| With light source | | Yes |
| With integrated diode | | Yes |
| Lamp holder | | None |
| Rated voltage Ue at AC 50 Hz | V | 85 - 264 |
| Rated voltage Ue at AC 60 Hz | V | 85 - 264 |

| | | |
|-----------------------------------|---|------------------|
| Rated voltage Ue at DC | V | 0 - 0 |
| Voltage type for actuating | | AC |
| Lamp type | | LED |
| Connection type auxiliary circuit | | Screw connection |
| Colour lamp | | White |
| Type of fastening | | Front fastening |