

Pushbutton, RMQ-Titan, Flat, momentary, black, Blank, Bezel: titanium



Part no. M22-D-S
216590
EL Number 4355306
(Norway)

Product name	Eaton Moeller® series M22 Pushbutton
Part no.	M22-D-S
EAN	4015082165901
Product Length/Depth	30 millimetre
Product height	30 millimetre
Product width	30 millimetre
Product weight	0.009 kilogram
Compliances	CE Marked
Certifications	IEC 60947-5 CSA Std. C22.2 No. 94-91 EN 60947-5 UL 508 CSA Std. C22.2 No. 14-05 VDE UL File No.: E29184 CE UL Category Control No.: NKCR IEC/EN 60947-5 CSA CSA Class No.: 3211-03 CSA File No.: 012528 IEC/EN 60947 CSA-C22.2 No. 94-91 VDE 0660 CSA-C22.2 No. 14-05 UL GL LR DNV
Product Tradename	M22
Product Type	Pushbutton
Product Sub Type	None
Bezel color	Chrome
Bezel material	Plastic
Color	Black
Design	Flat Classical
Fitted with:	Front ring
Inscription	Blank
Degree of protection	IP69K NEMA 13 NEMA 3R IP67 IP66 NEMA 4X NEMA 12
Degree of protection (front side)	NEMA 4X IP67/IP69K
Lifespan, mechanical	5,000,000 Operations
Opening diameter	22.5 mm
Operating frequency	3600 Operations/h
Product category	RMQ-Titan
Size	Front dimensions: 22 x 22 mm
Type	Pushbutton actuator
Mounting position	As required
Shock resistance	Mechanical, According to IEC/EN 60068-2-27

		30 g, Mechanical, According to IEC/EN 60068-2-27, Sinusoidal shock 11 ms
Ambient operating temperature - min		-25 °C
Ambient operating temperature - max		70 °C
Ambient storage temperature - min		40 °C
Ambient storage temperature - max		80 °C
Climatic proofing		Damp heat, constant, to IEC 60068-2-78 Damp heat, cyclic, to IEC 60068-2-30
Connection to SmartWire-DT		Yes With SWD-RMQ connections
Actuating force		5 N
Actuator color		Black
Actuator function		Spring-return Momentary
Force for positive opening - min		0 N
Equipment heat dissipation, current-dependent Pvid		0 W
Heat dissipation capacity Pdis		0 W
Heat dissipation per pole, current-dependent Pvid		0 W
Rated operational current for specified heat dissipation (In)		0 A
Static heat dissipation, non-current-dependent Pvs		0 W
10.2.2 Corrosion resistance		Meets the product standard's requirements.
10.2.3.1 Verification of thermal stability of enclosures		Meets the product standard's requirements.
10.2.3.2 Verification of resistance of insulating materials to normal heat		Meets the product standard's requirements.
10.2.3.3 Resist. of insul. mat. to abnormal heat/fire by internal elect. effects		Meets the product standard's requirements.
10.2.4 Resistance to ultra-violet (UV) radiation		Please enquire
10.2.5 Lifting		Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 Mechanical impact		Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 Inscriptions		Meets the product standard's requirements.
10.3 Degree of protection of assemblies		Does not apply, since the entire switchgear needs to be evaluated.
10.4 Clearances and creepage distances		Meets the product standard's requirements.
10.5 Protection against electric shock		Does not apply, since the entire switchgear needs to be evaluated.
10.6 Incorporation of switching devices and components		Does not apply, since the entire switchgear needs to be evaluated.
10.7 Internal electrical circuits and connections		Is the panel builder's responsibility.
10.8 Connections for external conductors		Is the panel builder's responsibility.
10.9.2 Power-frequency electric strength		Is the panel builder's responsibility.
10.9.3 Impulse withstand voltage		Is the panel builder's responsibility.
10.9.4 Testing of enclosures made of insulating material		Is the panel builder's responsibility.
10.10 Temperature rise		Not applicable.
10.11 Short-circuit rating		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 Electromagnetic compatibility		Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 Mechanical function		The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Technical data ETIM 8.0

Low-voltage industrial components (EG000017) / Front element for push button (EC000221)		
Electric engineering, automation, process control engineering / Low-voltage switch technology / Command and alarm device / Front element for push-button actuators (ecI@ss10.0.1-27-37-12-10 [AKF028014])		
Colour button		Black
Number of command positions		1
Construction type lens		Round
Hole diameter	mm	22.5
Width opening	mm	0

Height opening		mm	0
Type of button			Flat
Suitable for illumination			No
With protective cover			No
Labelled			No
Switching function latching			No
Spring-return			Yes
With front ring			Yes
Material front ring			Plastic
Colour front ring			Chrome
Degree of protection (IP), front side			IP67/IP69K
Degree of protection (NEMA), front side			4X