

Fuse-link, high speed, 400 A, AC 690 V, DIN 2, aR, DIN, IEC, dual indicator, live gripping lugs



170M5808D

Similar to illustration

Product name	Eaton Bussmann series high speed square body fuse
Part no.	170M5808D
EAN	5027590460262
Product Length/Depth	150 millimetre
Product height	72 millimetre
Product width	54 millimetre
Product weight	666 gram
Compliances	CE Marked RoHS Compliant
Certifications	IEC Rated UL Recognized
Product Tradename	None
Product Type	High speed square body fuse
Product Sub Type	None
Amperage Rating	400 A
Voltage rating	690 V (IEC), 700 V (UL)
Interrupt rating	200 kAIC
Class	Class aR
Clearing (I ₂ T)	79000 at 660 V
Application	Semiconductor, DC Common bus, DC drives, power converters/rectifiers
Fuse type	DIN 43620 Bladed
Fuse indicator	Combination fuse status indicator
Fuse size	2

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)

Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])

Fuse construction type according to IEC 60269	2
Type of current	AC
Rated voltage AC	V 690
Rated voltage DC	V
Rated current	A 400
Utilization category	aR (accompanied semiconductor protection)
Breaking capacity	kA 200
Colour code	None
Type of fuse status indicator	Combination fuse status indicator
Power loss at rated current	W 29
Mounting holes	
Centre-to-centre distance of connections	mm