

# TORES LED PC/PC 1500MM 10100LM 840 IP65 70W

DETAILED CARD



## TECHNICAL PARAMETERS

<b>Ingress protection:</b>	IP65
<b>Luminous flux [lm]*:</b>	10100
<b>Colour temperature [K]:</b>	4000
<b>Material of the body:</b>	PC
<b>Colour of the body:</b>	grey
<b>Diffuser material:</b>	PC
<b>Diffuser type:</b>	frozen
<b>Mounting version:</b>	surface, suspended
<b>Dimensions (H/W/T/S) [mm]:</b>	1500/85/80

## CHARACTERISTICS

Tores LED PC is a lamp dedicated to LED technology. Designed from scratch, it introduces new solutions to improve light distribution and temperature balance. Its very good technical parameters guarantee the achievement of the required level of illumination and energy savings. The lamp has a number of improvements to make installation easier and faster, such as adjustable brackets that provide an installation tolerance of +/-50 mm. As standard, it is equipped with durable stainless steel (INOX) clips. The lamp has a high IP65 rating, and the lamp body and shade are UV resistant.

## APPLICATION

Multifunctional surface-mounted LED lamp is designed for use in areas with high requirements for dust- and waterproofing. Particularly recommended for illuminating industrial facilities (factories, laboratories), warehouses, parking lots (underground and multi-level), sports stadiums, transport terminals and underpasses. The lamp is ideal for new lighting applications, as well as replacing traditional fluorescent fixtures with energy-efficient LED solutions.

# TORES LED PC/PC 1500MM 10100LM 840 IP65 70W

DETAILED CARD


## TECHNICAL PARAMETERS TABLE

<b>Index:</b>	374180	<b>LED lifespan L70B50 [h]:</b>	96000
<b>EAN:</b>	5905963374180	<b>LED lifespan L80B20 [h]:</b>	61000
<b>Light source:</b>	LED module	<b>LED lifespan L90B10 [h]:</b>	30000
<b>Rated power of the luminaire [W]:</b>	70	<b>Beam angle [°]:</b>	120
<b>Luminous flux [lm]:</b>	10100	<b>Diffuser material:</b>	PC
<b>Supply voltage [V]:</b>	220-240	<b>Diffuser type:</b>	frozen
<b>Frequency [Hz]:</b>	50/60	<b>Material of the body:</b>	PC
<b>Luminous efficacy [lm/W]:</b>	144	<b>Colour of the body:</b>	grey
<b>Energy efficiency class:</b>	C	<b>Dimensions (H/W/T/S) [mm]:</b>	1500/85/80
<b>Electrical protection class:</b>	I	<b>Ingress protection:</b>	IP65
<b>Colour temperature [K]:</b>	4000	<b>Mounting version:</b>	surface, suspended
<b>Colour rendering index:</b>	>80	<b>Working temperature [°C]:</b>	from -20 to +35
<b>SDCM:</b>	≤ 3	<b>Warranty [years]:</b>	5

Card creation date: 22 June 2023

The company reserves the right to make design changes or upgrades in the presented product. Product data sheet does not constitute an offer. \* Parameter tolerance is +/- 10%

 This product is a subject to electric and electronic waste equipment regulations (WEEE).

 Certificate CE - Nr: 171/2023

 **LENA**  
LIGHTING

Lena Lighting S.A.  
ul. Kórnicka 52, 63-000 Środa Wielkopolska  
tel. +48 61 28 60 333 (Pn-Pt, 8-16), e-mail: hello@lenalighting.pl, www.lenalighting.pl