

article#	3534620101P
article description	Wallbox GLB+ 22kW, cable Kabel Type2, 4G+bESingle
description long	<p>Wallbox GLB+ Charging Station for Electric Vehicles Connection: (230)400V AC, 50Hz, (1)3-phasig Number of charging units: 1 fixed charging cable 4,5 m with Type 2 connector Max. power per charging point: 22kW Charging current (min-max): 6A - 32A Nominal connection power: 22kW Protection: DC-fault protection (6mA) Access control: RFID Controller: CC612 charge controller Communication interface: 4G module Communication: OCPP 1.6 JSON, Modbus TCP Backend system: preconfiguration be.ENERGISED for immediate start-up WxHxD: 205x422x124 mm Material housing: plastic/ black Lockable cover Mounting method: Wall mounting Degree of protection: IP44 Impact strength: IK08 Ambient temperature: -25°C bis +40°C integrated digital modbus energy meter, certified acc. to MID directive Standards: accord. to EN 61851-1, IEC 61439-7</p> <p>be.ENERGISED Monitoring Package Single 104046701 1 pc. configuration instructions 1 pc. SIM card, 2 pcs. QR code 1 pc. instructions for activation, 2 pcs. RFID tags</p>
GTIN (EAN)	9003399459900
country of origin	SE
customs number	85371098
net weight	5.400 kg
minimum order quantity	1







<https://www.pcelectric.at/shop/en/?func=detail&artnr=3534620101P>

ETIM 9.0	EC002883
Installation side connection model	3-phase
Number of charging units	1
Max. power per charging point	22 kW
Nominal connection power	22 kW
Width	205 mm
Height	422 mm
Depth	124 mm
Mounting method	Wall mounting
Number of vehicle connectors Type 2	1
Material housing	Plastic
Degree of protection (IP)	IP44
Impact strength	IK08

