

# Product data sheet

Specifications



## Pragma flush enclosure - IP40 - 3x12 modules - 63 A - plain reversible door

10937

❗ Discontinued on: 15 October 2018

❗ Discontinued

### Main

Range	Pragma
Product or component type	Enclosure
Enclosure type	Modular enclosure
Width	330 mm embedded: 344 mm outside:
Height	585 mm embedded: 624 mm outside:
Depth	13.4 mm outside: 90 mm embedded:
Nb of 18 mm modules per row	12
Nb of horizontal rows	3
Provided equipment	2 x terminal block 1 x identification label
Type of door	Reversible Adjustable Plain

### Complementary

Enclosure mounting	Flush
9 mm pitches	24
Total number of 18 mm modules	36
[In] rated current	63 A
[Ui] rated insulation voltage	690 V
Type of rail	DIN
Cable entry	Flexible flaps
Number of terminal blocks	2 neutral / earth (screw connection) with 24 outgoing
Distribution block outgoing	12 x 25 mm <sup>2</sup> for neutral / earth 36 x 4 mm <sup>2</sup> for neutral / earth
Locking options description	Optional keylock
Enclosure material	Door: electro galvanised steel Enclosure: self-extinguishing plastic
Colour	Door: white (RAL 9016) Enclosure: white (RAL 9016)

---

<b>Market segment</b>	Residential Small commercial
-----------------------	---------------------------------

## Environment

---

<b>Fire resistance</b>	Enclosure: 650 °C
------------------------	-------------------

---

<b>Overvoltage category</b>	II
-----------------------------	----

---

<b>Ambient air temperature for operation</b>	-20...40 °C
--	-------------

---

<b>Standards</b>	IEC 60695-2-1 IEC 60439-3 DIN 43871
------------------	---

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number of Units in Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	11 cm
-------------------------	-------

---

<b>Package 1 Width</b>	35.3 cm
------------------------	---------

---

<b>Package 1 Length</b>	63 cm
-------------------------	-------

---

<b>Package 1 Weight</b>	4.2 kg
-------------------------	--------

---

## Contractual warranty

---

<b>Warranty</b>	18 months
-----------------	-----------

---

**Recommended replacement(s)**