

KL-15 terminal bar; 2 x 25 mm² + 13 x 16 mm², max. 63 A

Part no. **KL-15**
219726
EL Number **1782048**
(Norway)

General specifications

Product name	Eaton xComfort KLV LV systems Final Distribution Boards
Part no.	KL-15
EAN	9004852591137
Product Length/Depth	7 millimetre
Product height	9 millimetre
Product width	120 millimetre
Product weight	0.001 kilogram
Compliances	RoHS conform
Product Tradename	xComfort KLV
Product Type	LV systems
Product Sub Type	Final Distribution Boards

Delivery program

Type	Additional equipment BF flat distribution board KLV distribution board
Accessory/spare part type	General
Color	Other
Nominal current	63 A
Number of poles	Single-pole

Technical Data - Mechanical

Mounting method	Screw
Material	Metal
Number of inputs	2
Number of outputs	14
Connection type	Clamp Screwing
Conductor cross section, input - min	1.5 mm ²
Conductor cross section, input - max	25 mm ²
Conductor cross section, input AWG - min	0 mm ²
Conductor cross section, input AWG - max	0 mm ²
Conductor cross section, output - min	1.5 mm ²
Conductor cross section, output - max	16 mm ²
Conductor cross section, output AWG - min	0 mm ²
Conductor cross section, output AWG - max	0 mm ²

Additional information

Functions	Additional equipment
Suitable for	Fine strand conductors Solid conductors Stranded conductors
Used with	Individual KL screw terminal BF flat distribution board Accessory consideration KLV distribution board

Technical data ETIM 8.0

Energy distribution systems (EG000015) / Rail terminal bar (EC000275)	
Electric engineering, automation, process control engineering / Electrical insulation and connecting material / Energy distribution system / Rail terminal bar clamp (ecl@ss10.0.1-27-40-06-03 [AC0369011])	
Number of poles	1
Nominal current	A 63

Connection type		
Mounting method		Screw
Number of inputs		2
Number of outputs		14
Suitable for solid conductors		Yes
Suitable for stranded conductors		Yes
Suitable for fine strand conductors		Yes
Suitable for fine strand conductors without cable end sleeve		No
Suitable for extra fine-strand conductors		No
Suitable for extra fine-strand conductors without cable end sleeve		No
Conductor cross section, input	mm ²	1.5 - 25
Conductor cross section, output	mm ²	1.5 - 16
Conductor cross section, input AWG	mm ²	0 - 0
Conductor cross section, output AWG	mm ²	0 - 0
Contact safe		No
Height	mm	9
Width	mm	120
Depth	mm	7