


MEDO® 60

wall- and ceiling-mounted light, round,
2700/3000/4000K, 39W, trailing-edge phase, 110°, white

The new MEDO® sets standards and impresses with a longer service life, better energy efficiency and a higher indirect light component. The improved protection code IP50 and an outstanding CRI>90 colour reproduction index ensure exceptional quality. Three elegant casing colours and a CCT switch that enables you to choose between 2700 K, 3000 K and 4000 K lets you personalise your lighting situation. And thanks to EasyBase, installation is as simple as it is fast.



TECHNICAL DATA

Item no.	1007323
Number of different light outlets	2
IP Code	IP 50
Impact resistance class	IK 02
Impact resistance	0.2 Joule
Assembly	Surface
Assembly details	Ceiling,Ceiling with Acc.,Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	1000 mA
Safety class	I
Wattage	39 W
Ambient temperature	25 °C
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	27
Number of luminaires at LS C16A	33
Level of inrush current	12 A
Duration of inrush current	45 µs
Stroboscopic effect (SVM)	0.4
Lumen	4050/4250/4550 lm

Light Source

	
--	---

Accessories

1001952	MEDO 5m suspension , black
1001950	MEDO 5m suspension , white
135250	SUSPENSION SET , for MEDO round pendant, round, black, 5-wire
1001951	MEDO 5m suspension , silver-grey
135251	SUSPENSION SET , for MEDO round pendant, round, white, 5-wire
135254	SUSPENSION SET , for MEDO round pendant, round, silver-grey, 5-wire

Colour temperature	2700/3000/4000 Kelvin
Beam angle	110 °
Color	white
CRI	90
UGR ≤	22
LXXBXX data	L70B50
Service life	50000 h
Risk Group	1
Height	9.2 cm
Diameter	60 cm
Net weight	4.6 kg
Gross weight	4.922 kg