



NEW TRIA®

LED module, 3000K, 38°, PHASE, black

Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. A modular element is the 7W LED MODULE, which is available with different light colours (2700K/3000K) and beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI>90 ensure exceptional quality. In addition, the NEW TRIA® LED MODULE impresses with its service life of L80-B10@50,000h.

TECHNICAL DATA

Item no.	1007383
IP Code	IP 20
Assembly	Recessed
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	Leading edge, trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	200 mA
Wattage	8.3 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	35 °C
Number of luminaires at LS B16A	88
Number of luminaires at LS C16A	149
Level of inrush current	3 A
Duration of inrush current	30 µs
Stroboscopic effect (SVM)	0.4
Lumen	750 lm
Colour temperature	3000 Kelvin
Beam angle	38 °
Color	black
CRI	90
LXXBXX data	L80B10

Service life	50000 h
Risk Group	1
Height	3.9 cm
Diameter	5 cm
Net weight	0.12 kg
Gross weight	0.128 kg