




NEW TRIA® 68

recessed ceiling light, 2700K, 38°, IP 20, round, white

Discover the new generation of our NEW TRIA® recessed ceiling light with even more modularity for an individual lighting experience. Top sellers such as the NEW TRIA® 68 are also available as a complete set. The integrated LED MODULE, which is available with different light colours (2700K/3000K) and beam angles (38°/60°), provides lighting design options. The pivot range allows flexible alignment of the light. In black or white, the high-quality housing blends harmoniously into any room ambience. And thanks to the 68mm mounting ring supplied, the downlights can also be installed quickly and simply.



TECHNICAL DATA

| | |
|---------------------------------|-----------------------------|
| Item no. | 1007385 |
| Rotating or tilting | Tilttable |
| IP Code | IP 20 |
| Assembly | Recessed |
| Assembly details | Ceiling |
| Dimmable | Yes |
| Dimming technology | Leading edge, trailing edge |
| Primary nominal voltage | 220-240V ~50/60Hz |
| Secondary power / voltage | 200 mA |
| Safety class | II |
| Wattage | 8.3 W |
| Minimum ambient temperature | -20 °C |
| Maximum ambient temperature | 35 °C |
| Number of luminaires at LS B16A | 88 |
| Number of luminaires at LS C16A | 149 |
| Level of inrush current | 3 A |
| Duration of inrush current | 30 µs |
| Stroboscopic effect (SVM) | 0.4 |
| Lumen | 705 lm |
| Colour temperature | 2700 Kelvin |
| Beam angle | 38 ° |
| Color | white |

Light Source



| | |
|------------------------------|----------|
| CRI | 90 |
| LXXBXX data | L80B10 |
| Service life | 50000 h |
| Risk Group | 1 |
| Height | 4 cm |
| Diameter | 8.2 cm |
| Net weight | 0.18 kg |
| Gross weight | 0.193 kg |
| Shape of cut-out | round |
| Installation depth | 4 cm |
| Installation diameter | 6.8 cm |