



## NOBLO® SPOT

track system set, round, 2700K, 19W, trailing-edge phase, 32°, black

With the NOBLO® SPOT track system set you get everything you need for the perfect start. The set, available in several colour versions, includes two track sections, a central connector, two end caps and three NOBLO® SPOTS of the latest generation: high-quality spotlights made of aluminium with an improved CRI value (CRI>90), a lumen output of up to 126 lm/W and an increased service life of up to 50,000 hours. It's clear: with the new NOBLO® SPOTS, you are opting for a unique lighting experience.

## TECHNICAL DATA

Item no.	1007673
Number of different light outlets	3
Rotating or tilting	Rotary bar and tiltable
IP Code	IP 20
Assembly	Surface
Assembly details	Track Ceiling, Track Wall
Dimmable	Yes
Dimming technology	trailing edge
Primary nominal voltage	220-240V ~50/60Hz
Secondary power / voltage	150 mA
Safety class	I
Wattage	19 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	40 °C
Number of luminaires at LS B16A	128
Number of luminaires at LS C16A	160
Level of inrush current	3.5 A
Duration of inrush current	120 µs
Stroboscopic effect (SVM)	0.4
Lumen	2250 lm
Colour temperature	2700 Kelvin
Beam angle	32 °

## Light Source



<b>Color</b>	black
<b>CRI</b>	90
<b>LXXBXX data</b>	L80B10
<b>Service life</b>	50000 h
<b>Risk Group</b>	1
<b>Length</b>	200 cm
<b>Width</b>	5 cm
<b>Height</b>	12.5 cm
<b>Net weight</b>	1.8 kg
<b>Gross weight</b>	1.926 kg