

Power cable (N)YY RF



Application: Flexible cable for installation indoors, outdoors, in the ground, in water and in concrete.

Construction and technical data:

Standard:	VDE 0276-603, IEC 60502-1 with reference to
Conductor material:	copper, bare
Conductor construction:	Class 5 = flexible
Insulation:	PVC
Sheathing material:	PVC
Colour of outer sheath:	black
Flame-retardant:	yes
Max. temperature at conductor, °C:	70 °C
Permitted outer cable temperature, fixed, °C:	-5 - +70 °C
Permitted outer cable temperature, moved, °C:	-5 - +70 °C



The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.

(N)YY-O RF

Nominal voltage U₀:	0.6 kV
Nominal voltage U:	1 kV
Maximum permitted operating voltage in three-phase systems:	1.2 kV
Test voltage:	4 kV
Protective conductor:	no

part no.	part name		Rl [Ohm/km]	Wi [mm]	l _{bl} [A]	l _{be} [A]	L _b [mH/km]	R _{bv} [mm]	Ø [mm]	F _{zv} [N]	Cu	G [kg]
015250	1X35	RF	0.554	1.2	158	135	0.333	198	13.5	525	336	439
015251	1X50	RF	0.386	1.4	198	168	0.325	230	15.6	750	480	604
015252	1X70	RF	0.272	1.4	245	207	0.309	250	17.4	1050	672	805
015253	1X95	RF	0.206	1.6	292	250	0.302	277	19.9	1425	912	1044
015150	1X120	RF	0.161	1.6	344	292	0.294	307	20.8	1800	1152	1268

part no.	part name		RI [Ohm/km]	Wi [mm]	Ibl [A]	Ibe [A]	Lb [mH/km]	Rbv [mm]	Ø [mm]	Fzv [N]	Cu	G [kg]
015085	1X150	RF	0.129	1.8	391	335	0.29	337	23	2250	1440	1565
014766	1X185	RF	0.106	2	448	382	0.287	370	25.7	2775	1776	1894
011781	1X240	RF	0.0801	2.2	528	453	0.281	414	27.6	3600	2304	2600
011853	1X300	RF	0.0641	2.4	608	523	0.28	440	31.8	4500	2880	3029
015656	01X400	RF	0.0486	2.6	726	624	0.275	543	36.2	6000	3840	4151

RI	Conductor resistance
Wi	Insulation wall thickness
Ibl	Ampacity in air (30 °C)
Ibe	Ampacity in ground (20 °C)
Lb	Specific inductivity
Rbv	Bending radius, fixed installation
Ø	outer diameter approx.
Fzv	Tensile strength (during installation)
Cu	Copper weight (GER)
G	net weight per 1000