




## **VINOLINA ONE**

table lamp, battery, IP54, 2700K, TOUCH, black

VINOLINA ONE stands for mobile SLV table lamps that can be transported anywhere. With its timeless design, it emits an extremely cosy warm-white light (2700K) for up to 12 hours on a single charge. The aluminium light is available in white, black and an attractive rust look. The charging station and USB cable is included in the delivery. Experience an elegant lighting solution with the VINOLINA ONE, which is also dimmable via the touch switch.



## **TECHNICAL DATA**

| Item no.                                     | 1007359                                   |
|--|---|
| IP Code                                      | IP54                                      |
| Impact resistance                            | 0.35 Joule                                |
| Assembly                                     | Mobile                                    |
| Dimmable                                     | Yes                                       |
| Dimming technology                           | Touch                                     |
| Primary nominal voltage                      | 5V  |
| Safety class                                 | III                                       |
| Wattage                                      | 2.5 W                                     |
| Minimum ambient temperature                  | 0 ℃                                       |
| Maximum ambient temperature                  | 45 °C                                     |
| Temperature at glass (light emission)        | 50 °C                                     |
| Lumen  | 125 lm                                    |
| Colour temperature                           | 2700 Kelvin                               |
|  |   |
| Color  | black                                     |
| Color  | black<br>80                               |
|  |   |
| CRI  | 80  |
| CRI<br>LXXBXX data                           | 80<br>L80B10                              |
| CRI LXXBXX data Service life                 | 80<br>L80B10<br>50000 h                   |
| CRI LXXBXX data Service life Height          | 80<br>L80B10<br>50000 h<br>33 cm          |
| CRI LXXBXX data Service life Height Diameter | 80<br>L80B10<br>50000 h<br>33 cm<br>14 cm |