





WORKLIGHT PRO 150

pendant light, 150cm, 4000K, DALI, Touch, black

The new WORKLIGHT PRO stands for high performance in the workplace: the DALI-controllable pendant light is optimally designed in line with the latest DIN EN 12464:2021 standard. Its glare-free (UGR<19) luminous efficiency of 127 lm/W, a colour temperature of 4000K and improved, indirect light output offers everything you need for an ergonomic working environment. Dimmability and a long life-span of 50,000 hours also help to make the office pendant light what it is: a true SLV colleague that assists with productivity.



TECHNICAL DATA

Item no.	1007471
Number of different light outlets	2
IP Code	IP 20
Impact resistance class	IK 03
Impact resistance	0.35 Joule
Assembly	Surface
Assembly details	Ceiling
Dimmable	Yes
Dimming technology	DALI,Touch
Primary nominal voltage	200-240V ~50/60Hz
Secondary power / voltage	1400 mA
Safety class	I
Wattage	59 W
Minimum ambient temperature	-20 °C
Maximum ambient temperature	45 °C
Number of luminaires at LS B16A	37
Number of luminaires at LS C16A	37
Level of inrush current	5.1 A
Duration of inrush current	148 µs
Stroboscopic effect (SVM)	0.4
Lumen	7200 lm
Colour temperature	4000 Kelvin

Light Source

		Beam angle	80 °
		Color	black
		CRI	80
		UGR ≤	19
		LXXBXX data	L80B10
		Service life	50000 h
		Risk Group	0
		Length	150 cm
		Height	24 cm
		Depth	3.28 cm
		Pendant length	250 cm
		Net weight	6 kg
		Gross weight	6.42 kg