

# Bus cable EIB/KNX



**Application:** Due to the increased test voltage and the special marking the cable is designed as bus cable in the EIB/KNX facility control system according to EN 50090. For the Instabus itself is used only the red/black pair (transmission of 24 V supply voltage plus data packages), the second pair (white/yellow) is redundant. The cable may be installed on or under plaster, in ducts and installation channels in dry or wet rooms.

## Construction and technical data:

<b>Conductor material:</b>	copper, bare
<b>Conductor construction:</b>	Class 1 = solid
<b>Insulation:</b>	PVC TI1
<b>Stranding unit:</b>	pair
<b>Stranding:</b>	Layers
<b>Screen:</b>	plastic coated aluminium foil + solid copper drain wire
<b>Sheathing material:</b>	PVC YM1
<b>Flame-retardant:</b>	VDE 0482-332-1-2/IEC 60332-1-2
<b>Halogen-free:</b>	no
<b>Permitted outer cable temperature, fixed, °C:</b>	-30 - +70 °C
<b>Bending radius, fixed installation:</b>	15 x Ø
<b>Specific inductivity:</b>	0.68 mH/km



*The products and information presented here are for technical calculation only. They are subject to technical progress and in no way represent the ability of shipment. Outer diameters are approximately.*

## FABER<sup>®</sup> EIB

<b>Loop resistance:</b>	73.2 Ohm/km
<b>Maximum operating capacity:</b>	120 nF/km
<b>Test voltage:</b>	4 kV
<b>Core identification:</b>	colours acc. to VDE 0815
<b>peak operating voltage, V:</b>	250 V

part no.	part name	DI [mm]	Ø [mm]	Cu	G [kg]
101010	2X2X0.8 GN	0.8	6.3	21	55

part no.	part name	DI [mm]	Ø [mm]	Cu	G [kg]
101011	4X2X0.8 GN	0.8	8.8	41	92

DI	diameter conductor
Ø	outer diameter approx.
Cu	Copper weight (GER)
G	net weight per 1000