



DELTA style, Antracite cosso SCHUKO socket outlet 10/16 A 250 V with spring flap, increased touch protection cover plate 68 x 68 mm

Model	
product brand name	DELTA
product designation	SCHUKO socket outlet
cover version	central plate
design of the special power supply unit	without special current supply
design of the socket according to VDE 0620 for severe conditions	No
design of the phase tap	No
General technical data	
marking of socket outlet	without imprint
mounting type	fixing with claw and screw
surface processing	others
material	thermoplastic
Supply voltage	
operating voltage rated value	250 V
supply voltage frequency rated value	50 Hz
Protection class	
protection class IP	IP20
Main circuit	
operational current rated value	16 A
Appearance	
color	anthracite
Product details	
product component	
<ul style="list-style-type: none"> <li>• ejection equipment</li> <li>• labeling field</li> <li>• increased touch protection</li> <li>• residual current device</li> <li>• miniature fuse</li> <li>• integrated functional lighting</li> <li>• integrated light source</li> <li>• integrated orientation lighting</li> <li>• hinged lid</li> </ul>	<ul style="list-style-type: none"> <li>No</li> <li>No</li> <li>Yes</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>No</li> <li>Yes</li> </ul>
product feature	
<ul style="list-style-type: none"> <li>• lockable</li> <li>• halogen-free</li> <li>• transparent</li> </ul>	<ul style="list-style-type: none"> <li>No</li> <li>Yes</li> <li>No</li> </ul>
Product function	
product function	
<ul style="list-style-type: none"> <li>• socket selectable</li> </ul>	No

• overvoltage protection	No	
<b>Number</b>		
number of units	1	
number of sockets switchable	0	
<b>Connections</b>		
arrangement of contacts diagonal	No	
type of electrical connection	plug terminal	
<b>Mechanical Design</b>		
height	70 mm	
width	70 mm	
depth	45 mm	
fastening method	Unterputz	
material of the enclosure	plastic	
<b>Environmental footprint</b>		
Environmental Product Declaration (EPD)	Yes	
Global Warming Potential [CO2 eq] total	4.77 kg	
Global Warming Potential [CO2 eq] during manufacturing	0.284 kg	
Global Warming Potential [CO2 eq] during operation	4.48 kg	
Global Warming Potential [CO2 eq] after end of life	7.42E-5 kg	
<b>Approvals Certificates</b>		
<b>General Product Approval</b>	<b>other</b>	<b>Environment</b>



[Miscellaneous](#)

[Confirmation](#)

[EPD Typ II/III \(with life cycle assessment\)](#)

#### Further information

**Siemens has decided to exit the Russian market (see here).**

<https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business>

**Siemens is working on the renewal of the current EAC certificates.**

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

**Information on the packaging**

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5UB1842-0AC01>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5UB1842-0AC01>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5UB1842-0AC01](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5UB1842-0AC01)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

last modified:

11/1/2023

