

XLED home 2 XL S

V2 graphite

EAN 4007841 030056

Article number 030056



LED

3000 K



30 years (Ø 4,5h / day)

3000K warm-white

infrared sensor 180°

max. 10 m

IP44

Panel 180° hor., 180° ver.

Sensor 90° ver., 180° hor.

Light source not exchangeable

Control gear not exchangeable

2 - 2000 lux

Function description

Day-bright light in XL size. Powerful XLED home 2 XL S sensor-switched outdoor floodlight with 10 m sensor reach. Ideal for illuminating larger areas such as driveways, courtyards and gardens. Swivelling precision IR sensor covering 180°. Fully swivelling LED panel (180°, horizontally and vertically). Superior opal cover for optimum lighting. 2124 lm, 19,3 W, 180° angle of coverage, high thermal conductivity magnesium composite cooling system (HCMC).

Technical specifications

Dimensions (L x W x H)	161 x 180 x 240 mm
With lamp	Yes, STEINEL LED system
With motion detector	Yes
Manufacturer's Warranty	5 years
Settings via	Potentiometers
Version	graphite
PU1, EAN	4007841030056
Application, place	Outdoors
Application, room	outdoors, all round the building, terrace / balcony, courtyard & driveway
Installation site	wall, corner
Installation	Wall, corner, Surface wiring
Impact resistance	IK03
IP-rating	IP44
Protection class	II
Ambient temperature	-20 – 40 °C
Housing material	Plastic

Sneak-by guard	Yes
Capability of masking out individual segments	Yes
Electronic scalability	No
Mechanical scalability	No
Reach, radial	r = 5 m (39 m ²)
Reach, tangential	r = 10 m (157 m ²)
Photo-cell controller	Yes
Cover material	sticker
Luminous flux total product	2124 lm
Measured luminous flux (360°)	2124 lm
Total product efficiency	110 lm/W
Colour temperature	3000 K
Colour variation LED	SDCM3
Lamp	LED cannot be replaced
LED life expectancy (max. °C)	50000 h
Service life LED L70B50 (25°)	> 60000 h

XLED home 2 XL S

V2 graphite

EAN 4007841 030056

Article number 030056



Technical specifications

Cover material	Plastic, opal	Drop in luminous flux in accordance with LM80	L70B10
Mains power supply	220 – 240 V / 50 – 60 Hz		
Fluorescent lamps, electronic ballast	430 W		
Fluorescent lamps, uncorrected	500 VA	LED cooling system	HCMC (High Conductive Magnesium Composite)
Fluorescent lamps, series-corrected	900 VA	Twilight setting	2 – 2000 lx
Fluorescent lamps, parallel-corrected	500 VA	Time setting	8 s – 35 Min.
LED lamps < 2 W	16 W	Basic light level function	No
LED lamps > 2 W < 8 W	64 W	Twilight setting TEACH	No
LED lamps > 8 W	64 W	Output	19,3 W
Capacitive load in μ F	88 μ F	Colour Rendering Index CRI	= 82
Mounting height max.	4,00 m	Optimum mounting height	2 m
		Detection angle	180 °

Accessories

EAN 4007841 053086

Corner wall mount XLED Home 2 / Pro 240

Sensor-switched LED floodlight

XLED home 2 XL S


V2 graphite

EAN 4007841 030056

Article number 030056



Detection Zone




Mögliche Montagehöhe: 1,80 m – 4,00 m


Orange: radial

Schwarz: tangential

Dimension Drawing




Light Distribution Curve



Output	19,3 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Measured luminous flux (360°)	2124 lm
Colour temperature	3000 K
Colour Rendering Index	80-89
LED life expectancy (max. °C)	50000 h
LED cooling system	HCMC (High Conductive Magnesium Composite)

Master circuit diagram



Sensor-switched LED floodlight

XLED home 2 XL S


V2 graphite

EAN 4007841 030056

Article number 030056



Master/master interconnection circuit diagram



Master/slave interconnection circuit diagram

