

Sensor-switched LED indoor light

RS PRO P2 S

Emergency light - warm white
EAN 4007841 058586
Article number 058586



LED

30 years (Ø 4,5h / day)



high frequency sensor 360°



Ø 1 - 8 m

3000 K

3000K warm-white



IP54



2 - 2000 lux



5 sec - 15 min



Light source not exchangeable



Control gear not exchangeable



10% basic brightness

Function description

Circular classic. Perfect shape. Perfect efficiency. The perfect switched indoor light. The emergency-light version of the RS PRO P2 S integrates harmoniously into corridors, hallways and stairwells. It combines timeless design and extremely easy installation with pioneering technology and unbeatable efficiency. As many as ten lights can be interconnected by cable. Output: 15,1 W with 1674 lm, 3000 K.

Technical specifications

Dimensions (Ø x H)	320 x 110 mm	Soft light start	Yes
With lamp	Yes, STEINEL LED system	Functions	Emergency light in compliance with EN 60598-2-22 for 3h
With motion detector	Yes	Twilight setting	2 – 2000 lx
Manufacturer's Warranty	5 years	Time setting	5 s – 15 Min.
Version	Emergency light - warm white	Basic light level function	Yes
PU1, EAN	4007841058586	Basic light level function time	10/30 min, all night
Colour	white	Main light adjustable	No
Installation site	wall, ceiling	Interconnection	Yes
Installation	Ceiling	Interconnection via	Cable
Impact resistance	IK03	Lifetime LED according to IEC-62717 (L70)	100.000 h
IP-rating	IP54	Lifetime LED according to IEC-62717 (L80)	73.000 h
Protection class	II	Lebensdauer LED nach IES TM-21 (L70)	60.000 h
Ambient temperature	-10 – 40 °C	Lifetime LED according to IES TM-21 (L80)	60.000 h
Housing material	Plastic	Fuse protection B10	54
Cover material	Plastic, opal		
Mains power supply	220 – 240 V / 50 – 60 Hz		
Power consumption	136 W		

<https://www.steinell.de>

Subject to technical modifications

10.2023 Page 1 from 4

Sensor-switched LED indoor light

RS PRO P2 S

Emergency light - warm white
EAN 4007841 058586
Article number 058586



Technical specifications

Mounting height max.	4,00 m
Electronic scalability	Yes
Mechanical scalability	No
Reach, radial	Ø 8 m (50 m ²)
Reach, tangential	Ø 8 m (50 m ²)
Luminous flux total product	1674 lm
Total product efficiency	111 lm/W
Colour temperature	3000 K
Lamp	LED cannot be replaced
Base	without
LED cooling system	Passive Thermo Control

Fuse protection B16	87
Fuse protection C10	90
Fuse protection C16	145
LED lamps > 8 W	250 W
Capacitive load in µF	88 µF
Basic light level function in per cent	10 %
Output	15,1 W
Colour Rendering Index CRI	= 82
Luminous flux, emergency light	38 lm
Photobiological safety in accordance with EN 62471	RG1
Starting current, maximum	13 A
IP-rating, ceiling	IP54
Detection angle	360 °

Sensor-switched LED indoor light

RS PRO P2 S


Emergency light - warm white

EAN 4007841 058586

Article number 058586




Detection Zone




Possible mounting height: 2,00 m - 4,00 m
Orange: radial and tangential

Dimension Drawing




Light Distribution Curve



Output	15,1 W
With lamp	Yes, STEINEL LED system
Lamp	LED cannot be replaced
Measured luminous flux (360°)	1674 lm
Colour temperature	3000 K
LED life expectancy (max. °C)	50000 h
LED cooling system	Passive Thermo Control

Master circuit diagram



Sensor-switched LED indoor light

RS PRO P2 S


Emergency light - warm white

EAN 4007841 058586

Article number 058586



Master/master interconnection circuit diagram



Master/slave interconnection circuit diagram

