

Sensor-switched LED floodlight

Spot Garden SC

Sensor Connect
EAN 4007841 058685
Article number 058685



LED

20.000 h

3000 K

3000K warm-white



38°



infrared sensor 90°



max. 10 m



IP44



2 - 2000 lux (via App)



Light source replaceable by end user



Control gear not exchangeable



manual override 4h

Function description

Interconnected garden enjoyment. The Spot Garden SC ground spotlight with 90° infrared sensor simply pushes into the earth and provides versatile illumination all around the home. The LED spot is conveniently set, interconnected and controlled via Bluetooth by app. ON and OFF times, twilight and time settings as well as creating lighting group – all not a problem. 512 lm, 7,9 W, 3000 K. Includes 2.5 m mains plug and GU-10 LED.

Technical specifications

Dimensions (L x W x H)	140 x 69 x 369 mm	Mechanical scalability	No
With lamp	Yes, LED lamp	Reach, radial	r = 2 m (3 m ²)
With motion detector	Yes	Reach, tangential	r = 10 m (79 m ²)
Manufacturer's Warranty	3 years	Photo-cell controller	Yes
Settings via	Bluetooth	Luminous flux total product	512 lm
Version	Sensor Connect	Measured luminous flux (360°)	512 lm
PU1, EAN	4007841058685	Total product efficiency	64,8 lm/W
Application, place	Outdoors	Colour temperature	3000 K
Application, room	outdoors, garden	Colour variation LED	SDCM5
Colour	Anthracite	Lamp	LED can be replaced
Includes corner wall mount	No	Service life LED L70B50 (25°)	> 20000 h
Installation site	Ground spike	Soft light start	No
Installation	Ground spike	Continuous light	selectable, 4h
Impact resistance	IK03	Functions	Manual ON / ON-OFF, Timer, Master/slave override
IP-rating	IP44	Twilight setting	2 – 2000 lx
Protection class	I	Time setting	5 s – 60 Min.
Ambient temperature	-20 – 40 °C		

<https://www.steinel.de>

Subject to technical modifications

09.2023 Page 1 from 2

Sensor-switched LED floodlight

Spot Garden SC

Sensor Connect

EAN 4007841 058685

Article number 058685




Technical specifications

Housing material	Aluminium
Cover material	Plastic, transparent
Mains power supply	220 – 240 V / 50 – 60 Hz
Slave mode/selectable	Yes
Sneak-by guard	No
Capability of masking out individual segments	No
Electronic scalability	No

Basic light level function	No
Main light adjustable	No
Twilight setting TEACH	Yes
Interconnection	Yes
Interconnection via	Bluetooth
Output	7,9 W
Colour Rendering Index CRI	= 81
Detection angle	90 °

Detection Zone



Possible mounting height: -
Orange: radial
Black: tangential

Dimension Drawing

